

<b>Model Name</b>	<b>HS-1600T</b>
<b>Product Name</b>	<b>4-Channel HD/SD HDBaseT Portable Video Streaming Studio</b>
<b>Video Standard</b>	HD & SD
<b>Video Format</b>	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz
<b>Input Routable / Crosspoint</b>	N/A
<b>Video Input</b>	3 x HDBaseT 1 x HDMI
<b>Computer Graphic Interface</b>	1 via HDMI
<b>Down-Converted Output</b>	Yes
<b>Video Output</b>	3x HDMI PGM 1x STREAM (RJ-45)
<b>Audio Input</b>	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio
<b>Audio Output</b>	1x Stereo headphone
<b>Embedded Audio Support</b>	2 ch Audio embedded
<b>Audio Delay Calibration</b>	N/A
<b>A+V Switching</b>	N/A
<b>USK</b>	1x USK support Lumakey
<b>DSK</b>	N/A
<b>Picture in Picture</b>	1
<b>Logo Insertion</b>	N/A
<b>Built-in Audio Mixer</b>	Yes
<b>Built-in Monitor Display</b>	17.3" HD TFT LED backlit, 1920x1080 pix
<b>Built-in Intercom &amp; Tally</b>	N/A

<b>Streaming Video Encode</b>	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
<b>Streaming Audio Encode</b>	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
<b>Streaming Protocol</b>	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP (Publish)
<b>Streaming Control</b>	Web browser UI for configuration and control Socket commands
<b>Recording File System</b>	FAT, exFAT, NTFS
<b>Recording File Format</b>	MP4
<b>Recording Setting Control</b>	Web UI for system configuration and control
<b>Dimension (LxWxH)</b>	455 x 355 x 134 mm
<b>Weight</b>	17.2 Lbs (7.8 Kg), Reinforce Plastic Case
<b>Accessory</b>	CB-60/61/62