

Sound and Audio Combination Shielded and Unshielded

Description:

- Sound and audio special cable
- ASTM tinned copper
- PVC insulation
- Short overall twist lengths
- One pair shielded 100% coverage of aluminum polyester foil with 24 AWG strd. TC drain wire
- One unshielded Pair
- Overall PVC jacket
- Standard spool size 1000 feet



Rating as per NEC:

- NEC Type CMR
- (UL) - C(UL) or c(ETL)us Listed
- Constructed in accordance with UL Standard 444
- Listed as being resistant to the spread of fire as defined in section 800 – 51 (c) of the National Electric Code; UL 1666 Vertical Tray Flame Test.
- Meets 300 volt requirement as specified in section 800 – 51 of the NEC

Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power – Limited Control Circuits

Color Code:

Shielded Pair:

- 1. Black, 2. Red

Unshielded Pair:

- 1. White, 2. Green

Jacket: Gray

Special Notes:

+C(UL) CMR Canadian UL accepted mark replaces PCC–FT4

Mechanical Characteristics	
Number of Pairs	2 (1 shld, 1 unshld)
AWG Size	22
Stranding	(7 x 30)
Nom. Insulation Thickness	.010 (.25 mm)
Shield Type % Coverage	100% Aluminum Polyester Tape
Nom. Jacket Thickness	.015 (.38 mm)
Nom. O.D.	.168 (4.27 mm)
Drain Wire Size	24 (7 x 32)

Electrical Characteristics Nominal	
Capacitance @ 1 KHZ	55 pf/ft*
	180 pf/M*
	99 pf/ft**
	325 pf/M**
Conductor DCR (Resistance) @ 20° C	17 Ω per 1000 ft.

*Nominal Capacitance between conductors.
 **Nominal Capacitance between one conductor and the other connected to the shield.

This document is the property of WEST PENN WIRE. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE.



724-222-7060
 FAX: 724-222-6420