



N-Trance™: It's mesmerizing and bewitching, mood-altering and mind-blowing. It may even take you to another plane of existence.

It's an LED moving head fixture unlike any other. N-Trance™ is fitted with an ultra-bright 2° white LED for sharp beam effects, plus a stunning ring with 86x RGB 3-in-1 SMD5050 LEDs. You can perform captivating dual-layer effects and wield mastery over solid color changes, fade effects, and chase effects with speed control + variable tracer length. It also has full pixel mapping capabilities.

The beam has a 14-color wheel (+ white & split colors), plus a static gobo wheel with 21 gobos. It offers user-selectable 540/640° PAN and 270° TILT with fine 16-bit adjustments & speed control, 6/8-facet prism, and smooth dimming. Plus, you'll get 1-25Hz strobe + effects, auto mode, and sound active mode.

N-Trance™ has 3 user-selectable DMX modes (21/44/128 DMX channels) and features an intuitive 4-button control panel with high-resolution TFT LCD display. It comes with industry standard powerCON® connections, RJ45 In/Out, DMX 3/5-pin in/out jacks, and 2x quarter-turn Omega clamp brackets for quick and easy setup.

Make your next design spellbinding with N-Trance™.



Main Features

- 2° narrow beam effects via 90W LED
- LED ring with 86pcs RGB 3-in-1 SMD5050 LEDs
- Gobo wheel with 21 gobos + open
- Color wheel with 14 colors + open (split colors and bi-directional rotation)
- 6/8-facet bi-directional rotating prism
- Frost and color filter effects
- Independent DMX control of beam and LED ring effects
- Built-in auto/sound active programs
- Pan: 540/640°, Tilt: 270° (8-16 Bit Resolution)
- 1-25Hz fps strobe + variable/random effects
- 4 user-selectable dimming curves
- 2.4" TFT LCD display with 4 button control
- DMX512, Art-Net, RDM, M/S, sound active & auto mode
- 3/5-pin DMX In/Out + RJ45 etherCON In/Out (Art-NET)
- PowerCON™ compatible AC power In/Out
- Dimensions: 12.4 x 8 x 19.8 inches (315.3 x 202 x 502.5 mm)
- Weight: 31.3 lbs, 14.2 kg



Optical

90W white 7000K LED (2° beam)
86x RGB 3-in-1 SMD5050 LEDs (ring)
Flicker-free
Linear electronic focus
Luminous Intensity:
49,450 Lux @ 5M
12,721 Lux @10M



Movement

Pan: 540/640 degree (8-16 bit resolution)
Tilt: 270 degree (8-16 bit resolution)



Control

Protocol: USITT DMX-512
21/44/128-channel DMX modes
DMX512, Art-Net, RDM, M/S, auto, sound
3/5-pin DMX in/out
4-button 2.4" TFT LCD display menu



Power + Current

100-240VAC, 50-60 Hz
136W, 1.81A, PF: .62
PowerCON™ compatible AC power In/Out connectors



Warranty

2-year limited warranty, does not cover malfunction caused by damage to LEDs