





## PROTRON ECLYPSE



The PROTRON ECLYPSE™ is a versatile high powered 1000W air cooled IPX4 outdoor rated color blinder, strobe, wash luminaire. Features include (96) 10W CREE RGBW 4-in-1 LEDs, 31° beam / 63° field angles, 27,000+ total lumen output, brilliant eye candy effects, selectable pixel mapping zones, strobe intensity, duration, rate, and FX control, super high speed (1-25fps) adjustable strobe, DMX, RDM, Kling-NET, and Art-NET protocol support, 8/16 bit RGB and RGBW smooth color mixing modes, adjustable/removable yoke bracket with 3-position holes, interlocking system for multiple unit matrix designs, IP54 3/5pin DMX, RJ45 etherCON, Seetronic IP65 power in/out connections, 4-button control pane with OLED menu display, and a multi-voltage universal auto switching power supply (100-240v).

### FEATURES

- Versatile Color Blinder, Strobe, Wash Luminaire**
- High Powered 1000W Air Cooled IPX4 Outdoor Rated**
- 96 10W CREE RGBW 4-in-1 LEDs**
- 31° Beam / 58° Field Angles**
- 27,000+ Total Lumen Output**
- Brilliant Eye Candy Effects**
- Selectable Pixel Mapping Control Zones**
- Strobe Intensity, Duration, Rate, and FX Control**
- Super High Speed (1-25fps) Adjustable Strobe**
- DMX, RDM, Kling-NET and Art-NET Protocol Support**
- 8/16 Bit RGB and RGBW Smooth Color Mixing Modes**
- Adjustable/Removable Yoke Bracket w/3-Position Holes**
- Interlocking System for Multiple Unit Matrix Designs**



**IPX4 Outdoor Rated**

Specifications are subject to change without notice ©Elation Professional 02/05/19

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040  
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands  
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

**SPECIFICATIONS**

**SOURCE**

96 10W CREE RGBW 4-in-1 LEDs  
 15,000 Hour Average LED Life\*

\*May vary depending on several factors including but not limited to:  
 Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

**PHOTOMETRIC DATA**

31° Beam / 63° Field Angles  
 27,000+ Total Lumen Output

**EFFECTS**

Color Blinder, Strobe, and Wash  
 Brilliant Eye Candy Effects  
 Selectable Pixel Mapping Control Zones  
 Strobe Intensity, Duration, Rate, and FX Control  
 Super High Speed (1-25fps) Adjustable Strobe  
 8/16 Bit RGB and RGBW Smooth Color Mixing Modes

**COLOR**

RGBW

**CONTROL / CONNECTIONS**

Multiple DMX Channel Modes (24 total channels)  
 4 Button Touch Control Panel with OLED Menu Display  
 DMX, RDM, Kling-NET, and Art-NET Protocol Support  
 IP65 3/5pin DMX and RJ45 etherCON In/Out  
 IP65 Seetronic Power In/Out  
 Fixture-to-Fixture Interlocking Alignment Pins/Locks

**SIZE / WEIGHT**

Length: 24.9" (633mm)  
 Width: 7.0" (177.5mm)  
 Vertical Height: 14.4" (364.8mm)  
 Weight: 34.6 lbs. (15.7kg)


**ELECTRICAL / THERMAL**

AC 100-240V - 50/60Hz  
 843W Max Power Consumption  
 14°F to 113°F (-10°C to 45°C)

**APPROVALS / RATINGS**



**PIXEL MAPPING CONTROL ZONES**



**ORDERING INFORMATION**

PRODUCT ORDER CODE	
PRO951	PROTRON ECLYPSE
OPTIONAL ACCESSORIES ORDER CODES	
DRCSATPRO	Touring Road Case for Satura Profile
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
SCABLE60	Safety Cable 24" (610mm) 60 lbs. (27kg) Rating
STR527	5 ft. (1.5m) IP65 Seetronic 5pin PRO DMX Cable
NEU088	3 ft. (1m) powerCON TRUE1 Power Link Cable
CAT005	5' (1.5m) CAT6 etherCON Cable
	Additional cable lengths available

Specifications are subject to change without notice ©Elation Professional 02/05/19

