

Physical Parameter

Physical Parameter data

Pixel Pitch	1.26 mm
Pixel Configuration	1 red, 1 green, 1 blue
Configuration (LxH, per cabinet)	640x360 pixels
Diode Type	Surface Mount Device (SMD)
Dimensions (mm, LxHxD, per cabinet)	806.4x453.6x76.7mm
Dimensions (inch, inchxD, per cabinet)	36.4 inch x 2.95 inch
Weight	11.8kg

Optical Parameter

Optical Parameter data

Brightness (Peak/Max) ⁽¹⁾	1,200 nit / 600 nit
Contrast Ratio (Peak/Max) ⁽¹⁾	8,000:1 / 4,000:1
Viewing angle - Horizontal	160°
Viewing angle - Vertical	160°
Bit Depth	16bit per Color
Color Temperature - Default	6,500K
Color temperature - Adjustable	2,800 ~ 10,000K (use S/BOX)

Electrical Parameter

Electrical Parameter

Video Rate	50/60 Hz
Cabinet - Input Power Range	100~240 VAC, 50/60 Hz
Power consumption - Max	711 (W/m ²) / 260 (W/Cabinet)
Power consumption - Typical	237 (W/m ²) / 87 (W/Cabinet)
Heat Generation - Max(BTU/SF)	225 BTU/SF per hour
Refresh rate	3,840 Hz

Operation Conditions

Operation Conditions data

Working Temperature / Humidity	0°C~40°C / 10~80%RH
Storage Temperature / Humidity	-20°C~45°C / 5~95%RH
IP Rating	IP20
LED Lifetime (48nit)	100,000 hours to half brightness

Certification

Certification data

Certification	EMC Class B, Safety 60950-1
---------------	-----------------------------

Service

Service data

Service	Front(3) and Parts Rear(4)
----------------	----------------------------

Package

Package data

Box Dimension (WxDxH)	943 x 606 x 167
Box Volume (m3)	0.095
Package Weight (kg, per cabinet)	16.5kg

Disclaimer

Disclaimer data

Disclaimer⁽¹⁾	Peak Value according to IDMS (Information Display Measurement Standard)
Disclaimer⁽³⁾	Front Service : IFJ and IF-D offer Front Service to Power Supply/Main Board on a cabinet level
Disclaimer⁽⁴⁾	Parts Rear Service : IFJ and IF-D's Power Supply/Main Board can be accessed from the rear