

EPIX Flex Boost



CERTIFICATIONS/QUALIFICATIONS

- CE, MET
- IP Rating: IP65, outdoor/wet, with pressure equalizing M14 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- EPIX Flex Boost
- Seetronic Powerkon IP65 power cord

REQUIRED ACCESSORIES

- Accessories (required): Epix Flex Drive
- Compatible Mounting Options: M12 Bolt/Clamp
- Epix Flex 20

OPTIONAL ACCESSORIES

- Clamps
- IP Flex Cables

FEATURES

- IP65 outdoor rated in-line voltage booster for Epix Flex 20.
- Works when connected to the outputs of the Epix Flex Drive.
- Works to boost the in-line voltage to add additional Epix Flex 20's to the output of the Epix Flex Drive.

SPECIFICATIONS

CONSTRUCTION/PHYSICAL

- Dimensions: 11 x 7.5 x 5.25 in (279.4 x 190.5 x 133.35 mm)
- Weight: 4.4 lb (2 kg)
- Exterior Color: Black
- Housing Material: Metal

CONNECTIONS

- Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Device inputs: (1) 3-pin plastic screw connector
- Device Outputs: (1) 3-pin plastic screw connector
- Physical Linking: 2 inline EPIX Flex 20
- Cable Length (signal): 1.16 ft (0.355 m)
- Cable Length (power): 5 ft (1.5 m)

ELECTRICAL

- Input Voltage: 120/230 VAC, 50/60 Hz (switchable)
- Power and Current: 240 W, 2 A @ 120 V, 60 Hz
- Power and Current: 240 W, 1.04 A @ 230 V, 50 Hz