

## VS250 SVGA 3LCD Projector



# Portable projector with HDMI® for everyday business presentations.

More accurate, vivid color, even in well-lit rooms - 3,200 lumens of equal color and white brightness<sup>1</sup>

**SVGA resolution (800 x 600)** — ideal for projecting everyday presentations and graphics

Fast, easy setup with Epson - get up and running in no time with easy image adjustments and convenient control

**Remarkable color accuracy** — up to 3x Higher Color Brightness<sup>2</sup> and up to 3x Wider Color Gamut<sup>3</sup> with Epson® over DLP projectors

Works with the latest laptops and media players — supports HDMI, the standard in connectivity, for digital video and audio in one cable









### VS250 SVGA 3LCD Projector

#### **Specifications**

Projection System 3LCD, 3-chip technology Projection Method Front/rear/ceiling mount Driving Method Poly-silicon TFT Active Matrix Pixel Number 480,000 dots (800 x 600) x 3 Color Brightness¹ Color Light Output: 3,200 lumens

White Brightness¹ White Light Output: 3,200 lumens Aspect Ratio 4:3

Native Resolution 800 x 600 (SVGA)

**Resize Support** 1024 x 768 (XGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+)

Lamp Type 210 W UHE

Lamp Life<sup>5</sup> Up to 6,000 hours (Normal Mode) and up to 10,000 hours (ECO Mode)

Throw Ratio Range 1.45 (Zoom: Wide), 1.96 (Zoom: Tele) Size (Projected Distance) 30" - 350" (0.88 - 10.44 m) **Keystone Correction Auto** Vertical: ± 30 degrees

**Keystone Correction Manual** Horizontal: ± 30 degrees (Easy-Slide Horizontal Image Correction)

**USB Plug 'n Play** 

Projects audio and video, PC and Mac® compatible Contrast Ratio Up to 15,000:1

Color Reproduction Up to 1.07 billion colors

#### **Projection Lens**

Type Digital zoom (Manual)/Focus (Manual)

F-number 1.44

Focal Length 16.7 mm

Zoom Ratio Digital zoom 1.0 - 1.35

Display Performance NTSC: 480 lines; PAL: 576 lines (Depends on observation of the multi-burst pattern) Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/

Speaker 2 W (mono)

Operating Temperature 41 ° to 95 °F (5 ° to 35 °C) Power Supply Voltage  $100 - 240 \text{ V} \pm 10\%$ , 50/60 Hz

**Power Consumption** Normal Mode: 296 W ECO Mode: 211 W **Fan Noise** Normal Mode: 37 dR

Security Password Protect function

#### Dimensions (W x D x H)

Including Feet 11.9" x 9.2" x 3.2" **Excluding Feet** 11.9" x 9.2" x 3.0"

Weight 5.3 lb

ECO Mode: 28 dB

#### **Interfaces**

1x HDMI

Computer/component video: 1x D-sub 15 pin Composite video: 1x RCA (Yellow) Audio in: 1x RCA (White/Red) 1x USB connector Type A: PC-free USB and other 1x USB connector Type B: USB Plug 'n Play



#### **Remote Control**

Features Source search selection, power, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions

#### **Operating Angle**

Right/left: ± 30 degrees Upper/lower: ± 15 degrees

Operating Distance 19.7 ft (6 m)

#### **Eco Features**

RoHS compliant Recyclable product<sup>6</sup>

Epson America, Inc. is a SmartWay® Transport Partner<sup>7</sup>

#### Support

#### Epson Connection<sup>SM</sup>

Pre-sales support: U.S. and Canada 800-463-7766 Internet website: www.epson.com

Service Programs 1-year projector limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support and 90-day limited lamp warranty


#### What's in the Box

VS250 projector, power cable, computer cable (VGA), projector remote control, batteries, User Manual CD, Quick Setup Sheet

#### **Ordering Information**

VS250 Projector V11H838220 V13H010L96 Genuine Epson Lamp (ELPLP96) Replacement Air Filter (ELPAF32) V13H134A32 Soft Carrying Case (ELPKS69) V12H001K69 Universal Projector Ceiling Mount ELPMBPJF Duet™ Screen ELPSC80F ES3000 Screen (ELPSC26H) V12H002S3Y ES1000 Screen V12H002S4Y

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 2 Color brightness (color light output) in brightest mode, measured by a third-party lab in accordance with ISO 51.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016. | 3 Gamut volume in brightest mode, measured by a third-party lab in 3D in the CIE L\*a\*b\* coordinate space. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016. | 4 Based on TFCinfo: U.S. Projector Brand Customer Perception and Preference Study, Multimedia Projectors 2017. | 5 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | 6 For convenient and reasonable recycling options, visit www.epson.com/recycle | 7 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.





Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 **Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark, Duet is a trademark and Epson Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2017 Epson America, Inc. Com-SS-Oct-13 CPD-53758 6/17

#### Contact: