

# BrightLink® 710Ui WUXGA 3LCD Interactive Laser Display



## The world's first 3LCD ultra short-throw interactive laser display.

More accurate, vivid color, even in well-lit rooms -4,000 lumens of equal color and white brightness<sup>1</sup>

**Breakthrough laser technology** — provides up to 20,000 hours of virtually maintenance-free operation<sup>2</sup>; plus, get higher image contrast and Instant ON/OFF

**Full HD WUXGA display up to 100" diagonal** — optimal readability from anywhere in the room; 2x the interactive space of a 70" flat panel

**Pen- and touch-based interactivity** — allows up to eight users to draw, share and collaborate at once, with six points of touch plus two pens

**Enhanced wireless display technology** — connect up to 50 Chromebook<sup>™</sup>, Mac<sup>®</sup>, PC, iOS<sup>®</sup> and Android<sup>™</sup> devices, and simultaneously display up to four screens, with Epson iProjection<sup>™3</sup> (wireless module sold separately)

**Two-way content sharing** — teachers can push content from the projector to wirelessly connected devices and control which device screens to display; students can make notes and send their work back to the projector<sup>3</sup>

Includes 1-year subscription and support for SMART Learning Suite — SMART Notebook®, SMART amp $^{\text{\tiny{TM}}}$ , SMART lab $^{\text{\tiny{TM}}}$ , SMART Learning Suite Online and more

**DuoLink** — install two BrightLink displays side-by-side to create one seamless interactive surface up to 177" diagonal<sup>4</sup>







## BrightLink® 710Ui WUXGA 3LCD Interactive Laser Display

#### **Specifications**

Display System Epson 3LCD, 3-chip technology Display Method Ceiling/wall mount/table mount Driving Method Epson Poly-silicon TFT Active Matrix **Pixel Number** 2,304,000 dots (1920 x 1200) x 3 Color Brightness<sup>1</sup> Color Light Output: 4,000 lumens White Brightness¹ White Light Output: 4,000 lumens Interactive Color Brightness¹ Color Light Output: 4,000 lumens

Interactive White Brightness¹ White Light Output: 4,000 lumens

Aspect Ratio 16:10

Native Resolution 1920 x 1200 (WUXGA) Size (Projected) Area (16:10) 70.4" - 100" **Keystone Correction (Manual)** 

Horizontal: ±3 degrees Vertical: ±3 degrees

**USB Plug 'n Play** Mac OS X® 10.7/10.8/10.9/10.10/10.11/ macOS® 10.12.x

USB Plug 'n Play for Windows® Windows Vista®/Windows 7/Windows 8/Windows 10

Contrast Ratio Up to 2.500.000:1 Color Reproduction Up to 1 billion colors **Illumination Technology** Laser Phosphor Light Source Life<sup>2</sup>

20,000 hours (Normal) 30,000 hours (Extended)

#### **Projection Lens**

Type Manual focus F-number 1.6 Focal Length 4.2 mm

Throw Ratio Range (16:10) 0.22 - 0.37, (4:3) 0.33 - 0.44, (16:9)

**Zoom Ratio** Digital zoom: 1.0 – 1.35x

Display Performance NTSC: 480 lines PAL: 576 lines (Depends on observation of the multi-burst pattern)

Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM

Speaker 16 W monaural

Operating Temperature 32 ° to 113 °F (0 ° to 45 °C) **Power Supply Voltage** 100 – 240 V ±10%, 50/60 Hz **Power Consumption** 

ECO Mode: 348 W Normal Mode: 448 W Standby (Communication On): 2.0 W Standby (Communication Off): 0.3 W

**Fan Noise** 

Quiet Mode: 27 dB Normal Mode: 38 dB

Security Kensington lock provision, security anchor bar, password-protect function

#### Interactivity

Interactive Technology Infrared, 850 nm Interactive Area (Image Size) 70" – 100" diagonal (16:10,

#### **Interfaces**

2x HDMI

1x HDMI/MHL®

Computer/Component video: 1x D-sub 15 pin

Composite video: 1x RCA (Yellow)

Audio in: 2x Mini stereo USB connector: 1x Type B (USB display, audio and mouse

control interactivity)

USB connector: 2x Type A (USB memory/document camera) 1x RJ-45

Serial: 1x RS-232c Monitor Out: 1x D-sub 15 pin Audio Out: 1x Mini stereo Wireless LAN port: 802.11 b/g/n (not included) Interactive Synchronization Mini stereo In Interactive Synchronization Mini stereo Out

Touch Unit Connection Port

II **b** 0 **>** O 0 O

#### Interactivity (continued)

Interactive Modes Computer Interactivity/Input, PC-free and Whiteboard Annotation Mode, Pen: Dual User, Finger Touch: Up to 6 points of touch PC-free Annotation Two pens and two fingers Annotation Tools Epson Easy Interactive Tools, dual user

PC Annotation Sources USB, HDMI, Computer 1, Computer 2, LAN PC-free Annotation Devices Document cameras, DVD/Blu-ray Disc® player, iPod®/iPad® devices, Chromebooks

**Calibration Method** Automatic or Manual

Interactive Connectivity USB cable for non-networked Interactive Software Requirements Epson Easy Interactive Driver (Mac and PC — required for DuoLink); Windows and Linux: driver not required Mac: Mac OS X 10.7/10.8/10.9/10.10/10.11/ macOS 10.12.x Epson Easy Interactive Tools for Windows and Mac

System Compatibility Microsoft® Windows Vista SP2 (All editions except for Starter), Windows 8/8.1, Windows 10, Windows 7 SP1 (All editions except for Starter)

mac OS<sup>™</sup> 10.7/10.8/10.9/10.10/10.11/macOS 10.12.x, UBUNTU 15.10, 16.04 LTX, 16.10, 17.04

Gestures Requires Windows 7 or later, or or Mac OS 10.7 or later

#### **SMART Notebook Requirements**

Supported Operating Systems Windows 7 SP1, Windows 8/8.1, Windows 10, Mac OS X 10.9, 10.10, 10.11 Minimum Processor Intel® Core 2 Duo

Minimum RAM 2GB (4GB for UHD displays)

Minimum Hard Disk Space 3GB (Windows); 3GB (Mac)

#### **Interactive Input Device**

Type of Interactive Input Device Digital pen Interactive Pen Functions Mouse Functions (left and right click), Electronic pen, LED battery status indicator

Interactive Pen Power AA battery, rechargeable Compatible Pen Battery Types Eneloop® batteries (included), Manganese dry cell, alkaline dry cell

Interactive Pen Dimensions 6.3" x 0.94" (diameter) Interactive Pen Weight 1.1 oz (without battery)

#### Dimensions (W x D x H)

19.5" x 17.3" x 6.8' **Weight** 24.7 lb

#### **Remote Control**

Features Computer, Video/HDMI, USB, LAN, Source Search, Power, Aspect, Color Mode, Volume, E-Zoom, AV Mute, Freeze, Menu, Auto, Enter, ESC, Pointer, User, Home, Split, Pen Mode, Link Menu, ID, Page up, Page down

#### **Operating Angle**

Rear: Right/left: -55 to +55 degrees, Upper/lower: +75 to +15 degrees Front: Right/left: -30 to +30 degrees, Upper/lower: 0 to +60 degrees Operating Distance 19.7 ft (6 m)

#### **Eco Features**

Energy-efficient 3LCD light engine Recyclable product<sup>5</sup> Epson America, Inc. is a SmartWay® Transport Partner<sup>6</sup>

Service Programs 3-year projector limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support

#### What's in the Box

BrightLink 710Ui ultra short-throw interactive laser display, wall mount, mount template sheet, installation manual, finger-touch module, touch module mounting bracket, touch module cable, Quick Start Guide, power cable, USB A/B cable, electronic user manual, projector remote control, two (2) interactive pens, two (2) AA batteries (for interactive pens) plus battery charger, two (2) AA batteries (for remote), SMART Learning Suite redemption code

#### **Ordering Information**

BrightLink 710Ui	V11H877022
Air Filter	V13H134A43
PowerLite® Pilot™ 2 (ELPCB02)	V12H614020
Active Speakers (ELPSP02)	V12H467020
Wireless 802.11b/g/n LAN Unit (ELPAP10)	V12H731P02
100" Whiteboard	V12H831000
Interactive Pen A (orange)	V12H773010
Interactive Pen B (blue)	V12H774010
Replacement Pen Tips (hard/Teflon®)	V12H775010
Replacement Pen Tips (soft/felt)	V12H776010
Ultra Short-throw Wall Mount (ELPMB53)	V12H902020

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 2 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector comes with a 3-year limited warranty. | 3 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. | 4 Requires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com / 5 For convenient and reasonable recycling options, visit www.epson.com/recycle | 6 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

#### Better Products for a Better Future eco.epson.com

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 SmartWay
Transport Partner

**Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. BrightLink and PrivateLine are registered trademarks, Pilot is a trademark and Epson Connection is a service mark of Epson America, Inc. iPad, iPod, Mac, macOS and OS X are trademarks of Apple, Inc., registered in the U.S. and other countries. Android and Chromebook are trademarks of Google Inc. Microsoft, Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.

Copyright 2019 Epson America, Inc. Com-SS-Oct-13 CPD-54463R2 1/19

### Contact: