

ELATION® TVL PANEL DW™
DMX Channel Values / Functions (7 Total DMX Channels)

Supports Software Versions ≥: v1.1

Features subject to change without any prior written notice.

MODE / CHANNEL						VALUE	FUNCTION
2	3	4	5	6	7		
	1		1	1	1		WARM WHITE LEDS
						0-255	Warm White (0=Black - 255=100%)
	2		2	2	2		COOL WHITE LEDS
						0-255	Cool White (0=Black - 255=100%)
1		1			3		COLOR TEMPERATURE - LINEAR VARIABLE WHITE
						0	OFF
						1-255	3,200K - 5,800K (0=3,200K - 255=5,800K)
				3	4		SHUTTER / STROBE
						0-31	LEDs OFF
						32-63	LEDs ON
						64-95	Strobe Effect SLOW to FAST
						96-127	LEDs ON
						128-159	Pulse Effect SLOW to FAST
						160-191	LEDs ON
						192-223	Random Strobe SLOW to FAST
						224-255	LED ON
2	3	2	3	4	5		MASTER DIMMER INTENSITY
						0-255	Intensity 0 to 100%
		3	4	5	6		MASTER DIMMER INTENSITY FINE
						0-255	Dimmer Intensity FINE Adjustment
		4	5	6	7		DIMMER CURVES
						0-20	STANDARD
						21-40	STAGE
						41-60	TV
						61-80	ARCHITECTURAL
						81-100	THRATRE
						101-255	DEFAULT to UNIT CURVE SETTING

ELATION | **TVL PANEL DW™** | dmx traits

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu