

Motif™ atelier.8FX

RGB+WW Wash with Pixel Mapping + 10x40° Asymmetrical Beam

Rugged yet elegant... that's not just a description of the Blizzard Modern Interpretive Dance Troup. It also describes the Motif™ Atelier™ 8FX. Our IP65-rated half-meter LED linear wash light offers RGB+WW 4-in-1 LED color mixing and pixel effects via 8x 15W, individually controllable high output LEDs. It mimics tungsten-source lighting to produce soft, warm white tones or add more warmth to the blend of any RGB mixed color.

Motif™ Atelier™ 8FX innovative asymmetrical 10x40° optics are ideally suited for vertical wash applications along walls, scrims, and other boundaries. It projects a 10° soft edge parallel to minimize spill away. Atelier's™ 40° angle is perpendicular; its long axis mixes individual LEDs into a homogeneous wash or allows multiple swaths of color to overlap for spectacular gradients and pixel effects.

Motif™ Atelier 8FX features IP-rated DMX connectors and powerCON True1-compatible power connectors. Both power and DMX connectors also have sealing rubber covers to protect them from dust and water, making them fully compliant with IP65 protection class standards while making them easy to use indoors as well.

Luminous Intensity:

	2-meter		3-meter		4-meter		5-meter	
Beam	Lux	fc	Lux	fc	Lux	fc	Lux	fc
40°	2,251	209.1	1,037	96.4	589	54.7	337	35.0



IP65

SUITABLE FOR OUTDOOR USE

Main Features

- Color mixing via 8x 15W RGB+WW 4-in-1 LEDs
- 10-40° asymmetrical beam spread
- Wash effect, grouped pixels, and pixel mapping
- Virtual color wheel effects
- 33 built-in automated programs, 10 custom colors, and 3 custom program banks
- RGB+WW color mixing ability in standalone mode
- Custom global color calibration settings
- Variable electronic dimmer & multiple strobe effects
- Sync custom settings between fixtures via DMX
- Fixture ID addressing
- LED control panel with touch sensitive buttons
- Durable cast aluminum housing
- Tempered glass lens and watertight internal gaskets
- Efficient convection cooling for zero fan noise
- Mounting bracket with locking knobs



Optical

8x 15W RGB+WW 4-in-1 LEDs, (2700k Warm White)

10-40° asymmetrical degree beam

Flicker-free LEDs

Luminous intensity:
1,037 Lux (96.4 fc) @
2m | 242 Lux (22.5 fc)
@ 4m



Weight + Dimensions

Width: 20.6" (522 mm)
Depth: 3.7" (94.7 mm)
Height: 7.1" (179.9 mm)

Bracket depth: 5.2"
(132.3 mm)

Weight: 9.3 lbs. (4.2 kg)



Control

Protocol: USITT DMX-512

3/4/5/10/16/24/32 or
40-channel DMX

Standalone, master/slave,
color preset, auto mode

3-pin DMX input/output

4-button LED control
menu display



Power + Current

100-264VAC, 47-63 Hz

107W, .87A, PF: .99



Warranty

2-year limited warranty,
does not cover
malfunction
caused by damage to
LEDs