

Physical Parameter

IF025H-E

Physical Parameter data

Pixel Pitch	2.5 mm
Pixel Configuration	1 red, 1 green, 1 blue
Configuration (LxH, per cabinet)	192x216 pixels
Diode Type	Surface Mount Device (SMD)
Dimensions (mm, LxHxD, per cabinet)	480x540x65mm
Dimensions (inch, inchxD, per cabinet)	28.5 inch x 2.56 inch
Weight	5.8kg

Optical Parameter

Optical Parameter data

Brightness (Peak/Max) ⁽¹⁾	2,000 nit / 1,000 nit
Contrast Ratio (Peak/Max) ⁽¹⁾	10,000:1 / 5,000:1
Viewing angle - Horizontal	150°
Viewing angle - Vertical	150°
Bit Depth	16bit per Color
Color Temperature - Default	6,500K
Color temperature - Adjustable	2,800 ~ 10,000K (use S/BOX)

Electrical Parameter

Electrical Parameter

Video Rate	50/60 Hz
Cabinet - Input Power Range	100~240 VAC, 50/60 Hz
Power consumption - Max	620 (W/m ²) / 160 (W/Cabinet)
Power consumption - Typical	206 (W/m ²) / 54 (W/Cabinet)
Heat Generation - Max(BTU/SF)	196 BTU/SF per hour
Refresh rate	1,920Hz, 3,840 Hz Selectable

Operation Conditions

Operation Conditions data

Working Temperature / Humidity	0°C~40°C / 10~80%RH
Storage Temperature / Humidity	-20°C~45°C / 5~95%RH
IP Rating	IP20
LED Lifetime	100,000 hours to half brightness

Certification

Certification data

Certification	EMC Class A, Safety 60950-1
---------------	-----------------------------

Service

Service data

Service	Front and Rear
----------------	----------------

Package

Package data

Box Dimension (WxDxH)	606x667x179
Box Volume (m3)	0.073
Package Weight (kg, per cabinet)	9.1kg

Curve Installation

Curve Installation data

Concave	6000R
Convex	N/A

Disclaimer

Disclaimer data

Disclaimer⁽¹⁾	Peak Value according to IDMS (Information Display Measurement Standard)
---------------------------------	---