

Lighting Fixtures

- Black Fixture
- Available in 19°, 26°, 36° and 50° Beam Spreads
- 150 Total Watts
- 120W Edison LED
- LED Color Temperature: 3200K
- LED Lifespan: >50,000 Hours
- Center Beam Lux at 1 Meter Projection Distance:
 - 50°: 6500 lux, 36°: 11200 lux,
 - 26°: 12000 lux, 19°: 16900 lux
- High Quality Optical System
- Glass Reflector
- High Impact Plastic Housing
- FX Slot
- Available in White

FXLE1232W
LED Ellipsoidal LIGHTING FIXTURE



The FXLE1232W is a Dimmable LED ellipsoidal lighting fixture suitable for church, stage, theater, disco, night club, and other event and artistic applications. It has automatic stand alone control modes and can operate via a DMX-512 external signal.

SPECIFICATIONS			
Power Supply:	AC100V-240V, 50/60Hz	Electronic Strobe:	0-20Hz
Power Consumption:	Max. 150W	Electronic Dimmer:	0-100%
Switch Power Supply:	Built-in and Auto Switching	DMX In/Out:	3-Pin XLR
LED:	120W Edison	Display:	LED Display
LED Color Temp.:	3200K	Cooling Method:	3 Fans
LED Lifespan:	>50,000 Hours	IP Rating:	IP20
Control:	Auto, Master/Slave and DMX	Housing:	High Impact Plastic
DMX Channels:	2 Channels	Dimensions (LxWxH):	23.9" x 10.7" x 11.1"
		Weight:	12 pounds

	10'			20'			30'		
	Beam Dia. (WxH)	foot candle	lux	Beam Dia. (WxH)	foot candle	lux	Beam Dia. (WxH)	foot candle	lux
FXLE1232W19	3	972	10450	7	224	2410	10	102	1130
FXLE1232W26	4.5	658	7120	9.5	149	1620	14.5	70	770
FXLE1232W36	6	437	4520	12.5	105	1130	19	49	540
FXLE1232W50	10	219	2360	19	51	565	-	-	-

To view and/or download the Owner's Manual click here: www.lightronics.com/manuals/fxle1232wm.pdf