

ENCORE PROFILE 1000 COLOR™

#ENC132



Rear View

ENCORE PROFILE 1000 COLOR GOBOS



The ADJ Encore Profile 1000 Color is a modern 120W LED Ellipsoidal with an adjustable zoom range from 12 degree to 30 degree. It features a bright 120W LED source, 64 colors, variable strobe speed and dimming capabilities. Additional features include: adjustable zoom, shutters for manual framing and 3-pin and 5-pin DMX protocol. This fixture stays cool and consumes 144W of power.

Features:

- 120W RGBW Ellipsoidal with zoom
- 7 Operating Modes: RGBW Dimmer Mode, Color Change Mode, Color Fade Mode, Auto Run Mode, Static Color Mode, & DMX Controlled
- Master/Slave Mode
- 5 DMX Channel Modes: 4/5/6/10/11
- 64 Static Colors
- Includes 4 replaceable Glass Gobos
- 5 Dimmer Modes
- Typical Throw: 40 meter (12°) to 28 meter (30°)
- Strobing
- 0-100% electronic dimming
- Manual Zoom- 12-30 degree
- Manual focusing
- Manual Framing Shutters
- Fan Cooled
- Hanging Bracket
- UC IR Control (sold Separately) & Airstream IR Compatible (Transmitter Included)

Specifications:

- 1 x 120W RGBW 4-in-1 COB LED source
- Gobo Dimensions: Outer 61mm; Inner: 51mm; Thickness: 2mm
- 12° - 30° Beam angle
- Adjustable Pulse Width Modulation: 900 Hz, 1000 Hz, 1100 Hz, 1200 Hz, 1300 Hz, 1400 Hz, 1500 Hz, 25000Hz
- Gamma Adjustment: 2.0, 2.2, 2.4, 2.8
- White Color Balance Adjustment
- PowerCon In and Out
- 3 and 5 Pin DMX
- Power Consumption: 144W maximum
- Multi-voltage operation: AC 100-240V 50/60Hz (auto sensing)
- Dimensions (LxWxH): 22" x 9.75" x 15.25" / 560 x 250 x 385mm
- Weight: 19 lbs. / 8.5 kg.

Specifications subject to change without notice.



Photometrics

	0.5m	1m	2m	3m	4m	5m	Diámetro (Meters)
12°	0.11	0.22	0.44	0.66	0.88	1.10	
R	26100	7640	1898	807	452	289	(LUX)
G	21200	6230	1356	600	318	201	
B	22400	6340	1611	729	392	246	
W	9460	2900	773	338	186.3	111.5	
RGBW	81000	24000	4940	1822	1056	636	

	0.5m	1m	2m	3m	4m	5m	Diámetro (Meters)
30°	0.25	0.50	1.00	1.50	2.00	2.50	
R	5660	1824	470	197.1	116	68.7	(LUX)
G	4500	1202	344	147.1	77.3	50.4	
B	5240	1425	402	177.6	93.9	59.4	
W	2580	667	185	80.6	42.4	25.7	
RGBW	20200	4570	1160	506	268	175.3	

