

PROPAR™

cob RGBAW

200W RGBAW 5-in-1 LED PAR

ProPar™ COB RGBAW is packed with pro features, starting with its high-output 200W 5-in-1 RGBAW COB LED light source with a wide 45° beam angle for superior color mixing and coverage. It's equipped with a constant current LED driver to ensure smooth fades and a flicker-free performance in video applications.

You get easy access to its 22 built-in static colors including 7 white color temperatures ranging from 2700-9000K, 15 color macros with speed controllable color jumping and fade effects. It comes with auto mode, sound active mode, 1-20Hz strobe effects, and RGBAW color mixing; all directly accessible by using its 4-button LCD control panel, or via DMX with master slave capability.

ProPar™ COB RGBAW gives you complete control with 4 user-selectable dimming curve modes that give you smoother and slower dimming capabilities. It also has 2 separate dimmer response settings for either normal or halogen lamp emulation for more gentle changes in brightness.

It comes with dual mounting brackets with secure locking knobs, industry standard powerCON® compatible power input and output connections, 5-pin DMX input and output connections, and a 3/8" threaded down rod mounting point centered on the rear panel of the fixture.



Main Features

- 200W RGBAW COB LED, 100,000 hours
- RGBAW color mixing in standalone and DMX modes
- Built-in auto programs via master/slave, standalone
- Built-in sound active modes via master/slave, standalone
- Flicker Free, constant current LED driver
- Easy-to-use 4-button LCD digital control panel
- Wide 45° beam angle
- Heavy-duty composite housing
- 3/8" downrod mounting point connection
- Dual mounting yokes allow flexibility in positioning
- User selectable 2/3/5 or 10-channel DMX modes
- PowerCON® compatible AC input/output
- 5-pin DMX in/out connections

Luminous Intensity:

1M	2M	3M	4M	5M
12,178 lux	3,612 lux	1,607 lux	975 lux	609 lux
1131.3 fc	335.5 fc	149.3 fc	90.6 fc	56.6 fc



Optical

1x 200W RGBAW 5-in-1 COB LED, 100,000 hours

45° beam angle

Luminous intensity: 1,607 Lux (149.3 fc) @ 3m | 609 Lux (56.6 fc) @ 2m

Optional barndoors available (sold separately)



Weight + Dimensions

Width: 11.7" (288 mm)
Depth: 10.7" (272 mm)
Height: 8.4" (221.9 mm)

11.7 lbs. (5.3 kg)



Control

Protocol: USITT DMX-512

2/3/5 or 10-channel DMX modes

5-pin DMX in/out

4-button LCD display menu

Standalone, M/S, sound active, color preset



Power + Current

Operating Voltage: 100-240VAC, 50-60 Hz

Power Consumption: 187W, 2.4A, PF: .67



Warranty + Certifications

2-year limited warranty, does not cover malfunction caused by damage to LEDs

cETLus certified