



PT-12

4K60 4:2:0 HDMI Controller

| HDMI | 4K/60 UHD (4:2:0)



PT-12 is a CEC-enabled TV/display ON/OFF controller and extended EDID processor for HDMI signals up to 4K@60Hz (4:2:0) resolution. When PT-12 detects an HDMI cable plug, it automatically turns on the connected display, and automatically shuts down the display when signal loss is detected. PT-12 is an EDID processing tool for controlling the EDID functions

FEATURES

Plug-and-Play Display Operation - Simplifies meeting presentation operation by automatically turning ON/OFF a CEC-enabled display when the presentation source is plugged in / unplugged with user-defined shut-down delay

High-Performance HDMI Controller - Supports pass-through of signals up to 4K@60Hz (4:2:0) resolution with user control on signal capabilities and functions

HDCP Authorization - Controlled device appearance as HDCP authorized to allow unsecured content display by all market-available computer sources

Video Signal Control - Controlled color depth attributes and color space forcing capabilities of passing-through video signal, along with EDID locking configuration to ensure proper video display

Audio Signal Control - Controlled audio-channels limitation of passing-through audio signal

Display Control - Display auto shut-down upon no signal detection with user-defined delay, as controlled by end-user settings

Simple Operation - DIP-switches available for simple controller functions by end-user

Cost-Effective Maintenance - Status LED indicators for HDMI ports and power facilitate easy local maintenance and troubleshooting. Local device management and firmware upgrade via mini-USB port and DIP-switches, ensure lasting, field-proven deployment

Easy Installation - Compact PicoTOOLS® fan-less enclosure for device-back mounting, or side-by-side mounting of 4 units in a 1U rack space with the recommended Kramer rack adapter



TECHNICAL SPECIFICATIONS

Inputs	1 HDMI: On a female HDMI connector
Outputs	1 HDMI: On a female HDMI connector
Ports	1 USB: On a female mini USB connector
Video	Max Resolution 4K@60Hz (4:2:0) Max Data Rate: 10.2Gbps (3.4Gbps per data channel) Compliance: HDMI, HDCP 1.4
User Interface	Indicators: HDMI In, HDMI Out, Power LEDs Controls: 8 DIP-switches
Power	Source: 5V DC Consumption: 315mA
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Enclosure	Cooling: Convection Type: Aluminum Size PicoTools®
Regulatory Compliance (Standards Compliance)	Vibration ISTA 1A in carton (International Safe Transit Association) Safety: CE Environmental: RoHs, WEEE
Accessories	Included: Power supply, bracket kit
PRODUCT DIMENSION:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx

