

# GM212

## Technical Specifications

GB

Version 1.0 February 2006



# V-TONE

[www.behringer.com](http://www.behringer.com)



# V-TONE

**True Analog Modeling 120-Watt Guitar Workstation with 2 Independent Channels, each Featuring 27 Modeled Sounds**

GB

- ▲ Powerful 120-Watt 2-Channel Guitar Workstation with authentic V-TONE Analog Modeling
- ▲ Two original heavy-duty 12" BUGERA™ Vintage Guitar speakers for classic sound reproduction
- ▲ Authentic V-TONE Analog Modeling for 3 classic guitar amps, 3 speaker simulation models plus 3 gain modes—27 modeled sounds individually selectable per channel
- ▲ 2 independent, full-featured modeling channels offering everything you need from clean to crunch to super-fat distortion sounds
- ▲ Additional headphone output with integrated speaker simulation
- ▲ Dedicated CD input for playback of line-level signals (e.g. CD player, drum machine)
- ▲ FX loop for external effects devices (rack effects, stomp boxes, wah-wah pedals, etc.)
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

BEHRINGER

## SPECIFICATIONS

GM212	
<b>AUDIO INPUTS</b>	
GUITAR IN	1/4" TS, RF filtered
Input Impedance	approx. 1 MΩ unbalanced
FX INSERT RETURN	1/4" TS
Input Impedance	approx. 10 kΩ unbalanced
CD IN	RCA
Input Impedance	approx. 40 kΩ unbalanced
<b>AUDIO OUTPUTS</b>	
FX INSERT SEND	1/4" TS, low-impedance, line level
Output Impedance	approx. 100 Ω unbalanced
PHONES OUT	1/4" TRS stereo
Max. output level	+15 dBu / 100 Ω (+23 dBm)
<b>SYSTEM SPECIFICATIONS</b>	
power amp output	120 W / 4 Ω
<b>LOUDSPEAKERS</b>	
Type	2 x 12"
Model	BUGERA™ Vintage Guitar Series
Impedance	8 Ω
Power handling	70 W
<b>POWER SUPPLY</b>	
Mains voltage	USA/Canada 120 V~, 60 Hz
	Europe 230 V~, 50 Hz
	U.K./Australia 240 V~, 50 Hz
	Japan 100 V~, 50 - 60 Hz
	China/Korea 220 V~, 50 Hz
	General Export model 120/230 V~, 50 - 60 Hz
Power consumption	max. 200 watts
Fuses 100 - 120 V~	T 4 A H 250 V
Fuses 220 - 240 V~	T 2 A H 250 V
Mains connection	Standard IEC receptacle
<b>DIMENSIONS AND WEIGHT</b>	
Dimesions (H x W x D)	494 x 713 x 257 mm 19.5 x 28 x 10.1"
Weight	47.6 lbs ( 21.6 kg)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER Spezielle Studiotechnik GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903