



FiDO-4T-X

FiDO-4T-X offers unmatched flexibility and cost efficiency for SDI-Fiber conversion, allowing for long cable runs up to 10 km (32,808 ft) with electrical isolation - useful for eliminating ground loop problems.

\$2685 US MSRP

FiDO converters use a compact, low-profile enclosure that works well in tight spaces around and behind equipment racks, trucks and on camera.

<https://www.aja.com/products/fido-4t-x>

Video Formats

- 150 Mbps - 3 Gbps, format agnostic

Video Input Digital

- 4-channel independent 3G-SDI BNC Inputs, SMPTE-259/292/424

Video Output Digital

- 4-channel independent CWDM LC Fiber Outputs, SMPTE-259/292/424
- Nominal Wavelength:
 - SFP Option 1: 1271 nm & 1291 nm
 - SFP Option 2: 1311 nm & 1331 nm
 - SFP Option 3: 1351 nm & 1371 nm
 - SFP Option 4: 1391 nm & 1411 nm
 - SFP Option 5: 1431 nm & 1451 nm
 - SFP Option 6: 1471 nm & 1491 nm
 - SFP Option 7: 1511 nm & 1531 nm
 - SFP Option 8: 1551 nm & 1571 nm
 - SFP Option 9: 1591 nm & 1611 nm
- Optical Power: -5dBm (min), 0dBm (max)
- Extinction Ratio: 7.5dB (Typ)

*Please see SFP Configurator for CWDM wavelength choices

Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.966 Gbps, 2.970 Gbps - Auto Select
- All other rates are passed through and not reclocked

Size (w x d x h)

- 4.6" x 4.02" x 0.85" (117 x 102.11 x 21.6mm)

Weight

- 0.8 lb (0.4 kg)

Power

- 5 watts max
- Uses 5-20VDC power (AJA power supply model DWP-U-R1 included)

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)