




KUMO 3232-12G

KUMO 3232-12G offers increased capacity for larger configurations while maintaining a compact 2RU profile with support for 12G-SDI/6G-SDI/3G-SDI/1.5G-SDI with 32x 12G-SDI inputs and 32x 12G-SDI outputs.

\$3,995 US MSRP

KUMO 12G-SDI routers support large format resolutions, high frame rate (HFR) and deep color formats, while reducing cable runs when transporting 4K/UltraHD over SDI. The routers offer network-based and/or physical control, and mirror the physical form of AJA's production-proven KUMO 3232 and KUMO 1616 routers, with a new USB port for configuring IP addresses via AJA's eMini-Setup software. Built to the same quality standards as all AJA KUMO products, KUMO 3232-12G is the ideal choice for any situation where a balance of size and capacity are critical such as mid-sized post facilities and mobile trucks.

<https://www.aja.com/products/kumo-3232-12g>



Video Format

- 270 Mbps, 1.5 Gbps, 3 Gbps, 6 Gbps, 12 Gbps SDI
- 270 Mbps DVB-ASI
- Format agnostic, 270 Mbps - 12 Gbps

Video Input Digital

- 12G-SDI Inputs
- 32x 12G-SDI BNC, SMPTE-259/292/424/2081/2082

Video Output Digital

- 12G-SDI Outputs
- 32x 12G-SDI BNC, SMPTE-259/292/424/2081/2082
- Noninverting

Ancillary Data

- Passes all SDI embedded ancillary data including audio

Salvo

- Up to 8 Salvos can be configured and saved in each KUMO router

Cable Equalization

(Belden 1694A)

- 12Gbps, up to 50m
- 6Gbps, up to 100m
- 3Gbps, up to 170m
- 1.5Gbps, up to 200m
- 270Mbps, up to 390m
- Automatic operation

Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.967 Gbps, 2.970 Gbps, 5.934 Gbps, 5.940 Gbps, 11.868 Gbps, 11.880 Gbps - Auto Select
- All other rates are passed through and not reclocked

Switching Modes

- Single, Dual, and Quad link modes
- Switches in vertical blanking per SMPTE RP-168

Control Panel Compatibility

- AJA KUMO CP – 1RU X-Y Ethernet control panel
- AJA KUMO CP2 – 2RU X-Y Ethernet control panel

Reference Input

- External, 2x BNC
- Looping, nonterminating
- Blackburst or tri-level sync

Network Interface

- 1x RJ-45, 10/100/1000 Ethernet
- Supports AJA KUMO Ethernet control panels, direct connect or networked
- Basic support for Grass Valley Native Protocol
- Embedded web server for remote control

USB Interface

- 1x Mini-USB for IP configuration using AJA eMini-Setup

Serial Interface

- 1x DB-9 Female, RS-422
- Basic support for Grass Valley Native Protocol
- 9-pin D-connector pinout is as follows:

1	GND
2	TX-
3	RX+
4	GND
5	No Connection
6	GND
7	TX+
8	RX-
9	GND
Shell	GND

Size (w x d x h)

- 2RU - 17.4" x 1.54" x 3.50" (441.96 x 39.12 x 88.9 mm)

Weight

- 4.6 lb (2.1 kg)

Power

- 10-14VDC regulated, 20W typ, power supply required, included with purchase
- AC Adapter: 100-240VAC, 50/60 Hz, universal input

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)