



## 241

22/4 Unshielded CMR  
Audio and Control

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Insulation Thickness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.138 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	36 lbs
Bend Radius	1.242 in
Cable Weight	19 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



**241**

22/4 Unshielded CMR  
Audio and Control

**Related Products**

RELATED PRODUCTS	-
Plenum Number	25241B
Aquaseal Number	AQC240