

<b>Model Name</b>	<b>SE-650 Stream and Record GoKit</b>
<b>Product Name</b>	<b>(GO-650SR): 4-input HD switcher with H.264 streaming encoder/recorder and cables, inside a hand-carry case</b>
<b>Video Inputs</b>	2x HDMI, 2x HD-SDI
<b>Video Outputs</b>	2x HDMI (1 is MV, 1 is assignable- Recommend connect with NVS-30 video streaming) 1x HD-SDI (Assignable)
<b>Audio Inputs</b>	2x RCA Analogue (L/R) 2x Mono Microphone, De-embedded Digital Audio (2 CH)
<b>Audio Outputs</b>	2x RCA Analogue (L/R) 1x Stereo headphone (Mini Jack with volume control) Embedded Digital Audio (2 CH / Channel 1 & 2)
<b>Tally</b>	Yes, D-Sub -15 Male connector
<b>Software Update</b>	USB Port
<b>Audio Mixer</b>	
<b>Audio Fader</b>	5 VR, 6 CH (3 Pair) Audio Mixer
<b>Audio LED Meter</b>	2 Rows (Left / Right)
<b>Standards</b>	
<b>Supported Resolution</b>	1080i/50, 1080i/59.94, 1080i/60, 720p/50, 720p/59.94, 720p/60
<b>Internal Processing</b>	YUV 4:2:2, 10-bit
<b>Extras</b>	
<b>Keyers</b>	2 Keyers (2 Chroma Keyers), Linear as well as Luma Keying is supported
<b>Upstream Keyers</b>	2 (M/E Keyer & PIP)
<b>Chroma Keyers</b>	2 High Quality ChromaKeyers, available on Keyer & PIP
<b>PIP</b>	1x Full PIP, full size, position, crop control. Border with variable size & color
<b>Wipe</b>	32 Wipe Patterns including Circle, Heart. Full Softness control. Variable width Border with softness
<b>Stills</b>	Any unused channel can also be used as a still buffer, can store stills internally.

<b>Stinger Transitions</b>	Yes
<b>Logo</b>	1
<b>Operating Temperature</b>	0°C to 50°C (32°F to 122°F)
<b>Humidity</b>	10% to 80%
<b>Power Consumption</b>	12V / 29W
<b>Dimension (mm)</b>	400 x 264 x 72
<b>Weight</b>	1.72 Kg
<b>Video Streaming</b>	
<b>Video Input</b>	1x HDMI
<b>Supported Video Input Resolution</b>	1080p60/59.94/50/30/29.97/25/24/23.98 1080i29.97/25 720p60/59.94/50
<b>Video Output</b>	1x HDMI
<b>Audio Input</b>	HDMI embedded audio 1x 3.5mm phonejack
<b>Encode</b>	H.264 Baseline/Main/High
<b>Video Bitrate</b>	100Kbps~20Mbps Rec+Stream: 30Mbps
<b>Video Rate Mode</b>	VBR
<b>Audio Mode</b>	Stereo
<b>Audio Bitrate</b>	32~256Kbps
<b>Recording file format</b>	MOV, MP4
<b>Storage</b>	2x USB or 1x SD card
<b>Power Supply</b>	DC 5V 3A