



914

Stereo Power Amplifier (100 Watts per Channel)

| Speakers



The Kramer 914 is a high-performance 2x100W power amplifier that accepts a balanced stereo audio input on a 5-pin terminal block and converts the signal into a differential stereo audio output for speakers on a 4-pin terminal block

FEATURES

Stereo Mode - 2x100W @4Ω

BTL Mode - 1x200W @8Ω

ENERGY STAR® Compliant

Class D Amplifier

Input Level Sensitivity Adjustment

Remote Control - Volume, standby and mute

Audio Level Knob

Operating Modes - Stereo and bridged mono

Indicators - Independent left and right channel monitoring LEDs

Connectors - Easy-to-connect, detachable terminal blocks



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--|
| INPUT: | 1 balanced stereo +4dBu/10k Ω on a 5-pin removable terminal block |
| OUTPUT: | 1 stereo or bridged mono speaker output on a 4-pin removable large terminal block |
| INPUT SENSITIVITY: | 0.3V to 1.23V -10dBu to 4 dBu |
| OUTPUT POWER: | 2x100W @4 Ω , 2x50W @8 Ω , 1x200W @8 Ω BTL |
| AMPLIFIER TYPE: | Class D |
| MAXIMUM VOLTAGE GAIN: | 22.7dB |
| BANDWIDTH (-3dB): | 20Hz to 20kHz |
| S/N RATIO: | -70dB @ 14dBu amplification |
| CONTROLS: | Screw trimmer for line input sensitivity, remote 10k trimmer, contact-closure controls for mute and standby |
| AUDIO THD+NOISE: | 0.05% @75W RMS @4 Ω 6.67kHz |
| AUDIO 2nd HARMONIC: | 0.08% @75W RMS @4 Ω 6.67kHz |
| POWER SOURCE: | See label near rear panel power socket: USA version: 100-120V AC, 50/60Hz, 360VA; European version: 200-240V AC, 50/60Hz, 420VA |
| INCLUDED ACCESSORIES: | Power cord, mounting bracket |
| Product Dimension | 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H |
| Product Weight | 1.3kg (2.8lbs) approx |
| Shipping Dimension | 40.50cm x 29.70cm x 9.00cm (15.94" x 11.69" x 3.54") W, D, H |
| Shipping Weight | 1.7kg (3.8lbs) approx |

