

## Planar QE7550-T

## Interactive 4K LCD Display

The Planar® QE7550-T display connects a multitouch experience with stunning 4K image clarity. Offering an affordable solution for professionals who seek to collaborate or annotate using a large viewing area, Planar QE7550-T delivers the highest image resolution and enterprise-level features in conference rooms or huddle spaces, and is also ideal for public display applications such as way-finding, product catalogs and any interactive digital signage designed to promote customer engagement. The Planar QE7550-T offers 20 points of multi-touch and multi-user technology, making it easy for multiple users to collaborate and interact at the same time.



SPECIFICATION	DETAIL
Product Name	Planar QE7550T
Planar Part Number	997-8796-00
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	75 in. (diagonal)
Aspect Ratio	16:9
Display Active Area	65.0" (1650mm) x 36.5" (928mm)
Cabinet Dimensions (W x H x D)	67.4" x 39.0" x 3.6" (1711mm x 990mm x 92mm)
Bezel Width	1.22" (30.9mm) left/right; 1.23" (31.2mm) top/bottom
Protective Glass	ERO optically-bonded glass technology featuring Corning Gorilla Glass, 2mm AG
Brightness (typ)	500 nits
Response Time (typ)	6 ms
Frame Rate	120Hz
Contrast Ratio (typ)	1200:1
Contrast Ratio - Dynamic	20,000:1
Viewing Angle (typ)	178°
Color Gamut	72% NTSC
Display Color	>1 billion colors. Full 10 bit data path
Modes	3840x2160 @ 24/25/30/60Hz; 1920x1080 @ 24/25/30/50/60Hz; 480p, 576p, 720p @ 50/60 Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz
Pixel Pitch	0.429 mm

Weight	138 lb (63 kg)
Backlight	LED
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	195W (standby: <1W)
Operating Temperature	0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) at up to 3000m
Humidity	20 - 85% RH (non-condensing)
Approvals	FCC Class A, CE, cTUVus
External Connections	DisplayPort 1.2 x 1, HDMI 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2
Audio Output	PC Line Out, S/PDIF
Multi-Source Views	Quad only
Display Control	IR, RS-232, LAN, Keypad
Speakers	10W x 2 built-in
Orientation	Landscape/Portrait
Mounting	VESA: 600 x 400 mm
Installed Depth with Optional Wall Mount	7.1" (181mm)
Fanless	Yes
HD format	4K UHD 2160p
Display Technology	Edge-lit LED LCD
Touch Technology	IR 20 point touch
OS Compatibility	Windows 7, 8, 10, Mac OSX and Linux
Recommended Usage	Up to 24x7 operation
Warranty	3 years Advance Exchange
Options / Features	Embedded Planar ContentSmart Media Player and software (Compatible with only Microsoft® Windows® Vista, 7, 8 and 10), Scheduling, TAA compliant
Embedded Media Player: Resolution	UHD 4K (3840x2160) @ 60Hz
Embedded Media Player: Local Storage	16 GB flash memory
Embedded Media Player: Connections	Ethernet, USB x2
Embedded Media Player: Software	Planar ContentSmart Digital Signage Software (included). Compatible with only Microsoft® Windows® Vista, 7, 8 and 10.
Embedded Media Player: Operating System	Android
Embedded Media Player: Supported Video Codec	MPEG-1, MPEG-2, MPEG-4, VC-1, H.264 (AVC), H.265 (HEVC), HTML5, SMIL
Embedded Media Player: Supported Image Formats	JPEG, PNG

In the Box	QE7550T display, power cord, IR sensor, USB (A to B) cable, remote control, TouchMark license key and USB drive containing User Manual, touch drivers, and USB-to-serial driver
UPC	8 10689 00389 2

Specifications are subject to change without notice.

Specification Report Date: 10/2/2019

© Copyright 2019 Planar Systems, Inc. All rights reserved