

Model Name	DAC-75T
Product Name	HD Cross Converter with Touch Panel
Inputs	1 x VGA, 1 x HDMI, 1 x SD/HD-SDI, 1 x Analog Audio (Unbalanced)
Outputs	2 x SDI, 1x HDMI,
Setting Control	7" Touch Screen (Resolution 800x480)
Video Input Formats	<p>1 x SD/HD-SDI (YUV) 1080p 60/59.94/50, 1080p 30/29.97/25/24/23.98 1080psf 30/29.97/25/24/23.98 1080i 60/59.94/50, 720p 60/59.94/50 525i, 625i</p> <p>1 x HDMI (YUV/RGB) 1080p 60/59.94/50, 1080p 30/29.97/25/24/23.98 1080psf 30/29.97/25/24/23.98 1080i 60/59.94/50, 720p 60/59.94/50 480p, 576p, 480i, 576i 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz</p> <p>1 x VGA (RGB) 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz 1280x720@60Hz, 1920x1080@60Hz</p>
Video Input Formats	<p>SDI (YUV)/ HDMI(YUV) 1080p60/59.94/50, 1080p30/29.97/25/24/23.98 1080i60/59.94/50, 720p60/59.94/50 525i, 625i</p>
Video Process	SDI: YUV422 HDMI: YUV422/ YUV444/ RGB444
Audio Formats	<p>Input Unbalanced Analog Audio L/R : stereo audio SDI embedded audio : up to 8ch, 48KHz, PCM audio HDMI embedded audio : up to 8ch, 44.1/48/96KHz, PCM audio</p> <p>Output SDI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio up to 8CH, 48KHz, PCM audio</p>
Power	100~240V
Operating Temperature	0°C~50°C (32°F~122°F)

Humidity	10%~80%
Storage Temperature	-10°C~60°C
Dimension	280mm(L) x 300mm(W) x 70mm(H)
Weight	2.43Kg