

Phone (847) 498-9000 Fgix (847) 498-6691 Internet www.ampli.com **Portable Lectern**

ShowStyle Roving Rostrum S122A, SW122A, S132A, SW132A

Made in the U.S.A. Limited 6-year warranty

Formerly Perma Power

3149 MacArthur Blvd., Northbrook, IL 60062

Carry your lectern and sound system wherever you speak!

ShowStyle Roving Rostrum for crowds up to 1,500 in a 15,000 Sq. ft. room. Second speaker in lid. Forms a compact, rugged carrying case.

Amplifier Features

- ✔ Exclusive, 50-watt, AmpliVox Multimedia Amplifier. ✔ All 3 mic inputs (dynamic, condenser, Wireless) can See bottom of page for complete list of features and technical specs.
- 🖌 Auxiliary input jack for a CD player, tape player or 🖌 computer sound system. Capture your audiences attention with a mixed media presentation by adding music and sound effects. Separate tone and volume controls
- ✔ Line out jack for a tape recorder. You can record your presentation as it is happening.
- ✓ 2 speaker jacks for a total of 4 speakers possible (using Y-connector). Gives you true stereo sound.

Lectern Features

- ✔ Rugged molded ABS plastic case holds up to abuse ✔ Speakers may be placed up to 40-ft. apart for and still looks good.
- Ultra Portable! Use indoors or outdoors.
- Retractable legs.
- ✓ Two 6″ x 8" oval speakers; one speaker in ✔ Weighs only 18 lbs. Has easy-grip handle. lectern and one in lid.

- be used at the same time. Wireless mic kits sold separately. **Dual Wireless Capability** SW wireless series
- SW805A amplifier with built-in wireless receiver allows 2 people to be wireless simultaneously with second wireless mic kit
- ✓ Powered by 10 D-cell Alkaline batteries for up to 200 hours of talk time. Sold separately.
 - Never run out of power! International AC Adapter/Recharger (S1460) plugs into amplifier and converts to DC power or recharges NiCad Battery Pack. Sold separately.
- true stereo output and greater amplification.
 - Don't be caught with a faulty, incomplete or unfamiliar sound system. Take your lectern and sound system with you.

	ShowStyle Roving Rostrum Wireless ShowStyle Roving Rostrum (as above with SW805A Amplifier with	. List ^{\$}	693
01112211	built-in wireless receiver and with wireless headset & lapel mics and transmitter)	. List ^{\$}	991
S132A	ShowStyle Roving Rostrum Plus (same as \$122A with CD and tape player)		
SW132A	Wireless ShowStyle Roving Rostrum Plus (as above with SW805A Amplifier		
	with built-in wireless receiver and with wireless headset & lapel mics and transmitter)	. List ^{\$} 1	1,107
S1100	Reading Lamp (clip-on AC lamp with 8-ft. cord; 25-watt bulb included)	. List ^{\$}	58
S1460	International AC Adapter/Recharger (110/240V; 50/60 Hz; 9-ft. cord)	. List ^{\$}	114
S1465	NiCad Battery Pack	. List ^{\$}	173
S1600	Wireless Lapel Mic Kit (lapel mic, transmitter, receiver)	. List ^{\$}	314
S2030	Lapel Mic (condenser; 40" cord, 12-ft extension)		58
S2040	Headset Mic (40" cord, 12-ft. extension)	. List ^{\$}	58





Great sound in a small, portable package. Light, rugged case packs everything to go wherever you Lapel mic (optional) leaves hands free for go. slides, pointer, visual demonstrations, etc.



2 speakers - one in lectern and one in lid for remote placement.

Power and portability for a variety of speaking need. The Show- Style Roving Rostrum goes wherever you go.

Technical Specs

Amplifier Model S805A. 50 watts nominal output; 25 watts per channel. All integrated circuit design.

Power Controls On-off switch with LED power indication light. Jack for optional, external AC adapter/recharger.

Power Source 10 fresh D-cell Alkaline batteries (not included) provide 200 hrs. operation for up to a full year's use. 110/240V AC Adapter/recharger available (S1460).

Auxiliary Input Stereo jack with separate volume and tone controls. For tape, CD, computer sound card

Microphone Model S2030A. Professional lowimpedance, cardioid pattern, dynamic microphone, steel case, frequency response 50-15,000 Hz; with 15-ft cable; adjustable, shock-mount, gooseneck. On-off switch.

Microphone Jacks 1 each dynamic, condenser with phantom power and wireless. Microphone volume control adjusts all mics together. All 3 mic inputs and auxiliary input can be used at the same time

Speakers Two 6" x 8" oval speakers; 1 in lectern and 1 in lid.

Speaker Jacks 2 jacks; 1 per line input channel. Each jack can drive 4- or 8-ohm speakers. Mic inputs are added equally to left and right channels. Output driver is placed into standby mode when its output jack is empty, reducing power drain and prolonging battery life.

Lamp S1100 (optional). 25-watt clip-on AC lamp with 8-ft. cord. Bulb included.

Construction Scuff-resistant, molded black luggage-type plastic; retractable legs for height adjustment

Dimensions 16.75"W x 17.25"D x 8.875"H: