# **BA210**

# **Technical Specifications**

Version 1.1 September 2004




ULTRABASS



# **ULTRABASS**

High-Performance 500-Watt Bass Cabinet with Original 2 x 10" BUGERA™ Aluminum Cone Speakers and 1" Horn Driver



- ▲ Original BUGERA™ HARD ATTACK Aluminum Cone Speakers
- ▲ Ultra-fast, direct response and incredible attack
- ▲ Switchable 1" custom-made horn tweeter for high-end punch
- ▲ Unique tweeter remote control via footswitch or BEHRINGER MIDI FOOT CONTROLLER FCB1010
- ▲ Input and link outputs on 1/4" TS and professional speaker connectors (compatible with NEUTRIK® SPEAKON®), impedance 8 Ohms
- ▲ Recessed carrying handles and integrated rollers for easy transportation
- ▲ Shock proof metal grille, reinforced corners and rugged carpet covering
- ▲ Exceptionally rugged construction for long life and durability
- Conceived and designed by BEHRINGER Germany

## **ULTRABASS BA210**

### **SPECIFICATIONS**

High-power bass speakers 2 x 10" BUGERA™

Aluminum cone speakers 95 dB @ 1 W / 1 m

Sensitivity 95 dB @ 1 W / Impedance 8 Ohm

Impedance 8 Ohm
Frequency response 42 Hz - 16 kHz

Power (RMS / Music) 500 W

Tweeter 1" tweeter driver

**SPEAKER CONNECTIONS** 

Input/Link

2 professional speaker connectors, compatible with NEUTRIK® SPEAKON® (wired in parallel) as well as one 1/4" TS

connector

DIMENSIONS/WEIGHT

Dimensions (W x H x D) 655 mm (25 4/5") x

500 mm (19 7/10") x 366 mm (14 2/5")

**Weight** ca. 28.5 kg (62.8 lb)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or shown.

### **ULTRABASS BA210**

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. NEUTRIK®, SPEAKON® as well as the names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2004 BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany Tel. +49 2154 9206 0, Fax +49 2154 9206 4903