

# SONY



3LCD Laser Projectors

**VPL-FHZ120L** (12,000lm, WUXGA)

**VPL-FHZ90L** (9,000lm, WUXGA)



The latest in high-brightness laser projectors.  
Ideal for large venues, mid-sized classrooms and conference rooms.



For auditoriums/halls



For classrooms/conference rooms



For museums

# SPECIFICATIONS

		VPL-FH2120L	VPL-FH290L	
Display system		3 LCD system		
Display device	Size of effective display area	1" x 3 BrightEra LCD Panel, Aspect ratio: 16:10		
	Number of pixels	6,912,000 (1920 x 1200 x 3) pixels		
Projection lens	Focus, Zoom	Powered / Manual (Depend on lens)		
	Lens shift	Powered / Manual	Powered	
Light source	Type	Laser diode		
Auto filter cleaning / Auto color calibration		Yes / Yes		
Light output*1 (Mode: Standard / Middle / Low)		12,000 lm / 10,000 lm / 8,000 lm	9,000 lm / 8,000 lm / 7,000 lm	
Constant ratio*1		∞ : 1		
Color space	Picture mode: sRGB	sRGB 100%	—	
Reality Creation Image Processing		Yes		
Displayable scanning frequency	Horizontal / Vertical	15 kHz to 92 kHz / 48 Hz to 92 Hz		
Display resolution	Computer signal input	Maximum display resolution: 1920 x 1200 dots		
	Video signal input	480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i The following items are available for digital signal only; 1080/60P, 1080/50p, 1080/24p, 1080/30p*3		
Keystone correction (Max.)	Horizontal / Vertical	+/- 30 degrees / +/- 30 degrees		
INPUT / OUTPUT (Computer / Video / Audio)	INPUT A	RGB/Y Pb Pr input connector: 5BNC (female)		
	INPUT B	RGB input connector: Mini D-sub 15-pin (female)		
	INPUT C	DVI input connector: DVI-D 24-pin (single link), HDCP support		
	INPUT D	HDMI input connector: HDMI 19-pin, Digital RGB/Y Pb Pr, HDCP support		
	INPUT E	HDBaseT interface connector: RJ45, 3 play (Video, LAN(100BASE-TX), RS-232C)		
	INPUT F	Optional adaptor slot (For 3G-SDI Input Adaptor BKM-PJ20)	—	
	INPUT G	HTML Viewer		
	OUTPUT 1	Monitor output for Input A / Input B Connector: Mini D-sub 15-pin (female)		
	USB	Type-A x 1		
	INPUT / OUTPUT (Others)	REMOTE	D-sub 9-pin (male) / RS232C	
LAN		RJ45, 10BASE-T / 100BASE-TX / 1000BASE-T		
Acoustic noise (Mode: Standard)*2		42 dB	39 dB	
Operating temperature / Operating humidity		32°F to 109°F (0°C to 45°C) / 20% to 80% (no condensation)		
Storage temperature / Storage humidity		14°F to +140°F (-10°C to +60°C) / 20% to 80% (no condensation)		
Power requirements		AC 100 V to 240 V, 10.8 A to 4.4 A, 50 Hz to 60 Hz	AC 100 V to 240 V, 8.4 A to 3.4 A, 50 Hz to 60 Hz	
Power Consumption (Maximum)	AC 100 V to 120 V	1076 W	840 W	
	AC 220 V to 240 V	1033 W	814 W	
Power Consumption (Standby mode)	AC 100 V to 120 V	0.50 W (when "Standby mode" is set to "Low")		
	AC 220 V to 240 V	0.50 W (when "Standby mode" is set to "Low")		
Power Consumption (Networked Standby mode)	AC 100 V to 120 V	21.6 W (LAN) / 26.5 W (HDBT) / 26.6 W (ALL Terminals and Networks Connected, when "Standby Mode" is set to "Standard")		
	AC 220 V to 240 V	21.3 W (LAN) / 26.5 W (HDBT) / 26.6 W (ALL Terminals and Networks Connected, when "Standby Mode" is set to "Standard")		
Heat dissipation	AC 100 V to 120 V	3671 BTU / h	2866 BTU / h	
	AC 220 V to 240 V	3524 BTU / h	2777 BTU / h	
Dimensions (W x H x D) (without protrusions)		Approx. 21 13/32 x 8 1/16 x 22 7/32 inches (544 x 205 x 564 mm)		
Weight (without optional projection lens)		Approx. 58 lb (27 kg)	Approx. 26 kg (58 lb)	
Supplied accessories	Remote commander	RM-PJ30		
Optional accessories	Projection Lens	VPLL-4008 / Z4111 / Z4015 / Z4019 / Z4025 / Z4045		
	Option Slot	BKM-PJ20 (Poh 3G-SDI Input)		

\*1 Value is in accordance with ISO 21118, and may differ depending on the actual unit. Brightness and contrast vary depending on use conditions and environments.  
\*2 The figures are approximate. They vary depending on the environment or how the projector is used. \*3 When using BKM-PJ20 (for VPL-FH2120L)

## OPTIONAL LENS INFORMATION

	Throw ratio	Lens shift range	
		Vertical	Horizontal
VPLL-4008	1.00:1	+/- 32%	+/- 15%
VPLL-Z4111 (New)	1.30:1 to 1.96:1	+/- 99%	+/- 51%
VPLL-Z4015	1.85:1 to 2.44:1	+/- 98%	+/- 51%
VPLL-Z4019	2.41:1 to 3.07:1	+/- 107%	+/- 57%
VPLL-Z4025	3.02:1 to 5.58:1	+/- 107%	+/- 57%
VPLL-Z4045	5.56:1 to 7.5 :1	+/- 107%	+/- 57%

Visit [sony.com/laser](http://sony.com/laser) for more information

### LASER NOTICES

For the U.S.A.  
IEC 60825-1:2007 CLASS 3R  
LASER PRODUCT



©2017 Sony Corporation. All rights reserved.

Reproduction in whole or in part without written permission is prohibited.

Features and specifications are subject to change without notice.

The values for weight and dimension are approximate.

"SONY" is a registered trademark of Sony Corporation.

"Z-Phosphor", "BrightEra" and "Remote Commander" are trademarks of Sony Corporation.

Trademark PJLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas.

The terms HDMI and HDMI High-Definition Multimedia Interface,

and the HDMI Logo are trademarks or registered trademarks of

HDMI Licensing LLC in the United States and other countries.

All other trademarks are the property of their respective owners.

HDBase™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.

Please visit Sony's professional website or contact your Sony representative for specific models available in your region.

Sony Electronics Inc.  
115 West Century Road  
Suite 250  
Paramus, NJ 07652  
[sony.com/laser](http://sony.com/laser)

DI-0344-A (MK20244V2)

Issued in USA (11/18)