



Configuration:

ATT-UJ Universal Attenuator with 3.5mm & 1/4" Jack Cables

Product Overview:

The ATT-UJ universal attenuator is designed to interface a 100 V line or low impedance (low Z) speaker systems to various inputs such as those found on Hearing Loop equipment. In addition to transformer isolation, a range of attenuations are possible by connecting to the appropriate output terminals.

Highlights:

- Input signal adaptor in interface a 100 V line or low impedance (low Z) speaker systems to an hearing loop driver.
- Includes a 3.5mm and 1/4" to raw ended cables.

Includes:

- One (1) ATT Universal Attenuator
- One (1) Mono 3.5mm to Raw End Cable
- One (1) Stereo 1/4" to Raw End Cable

Product Specification: Universal Attenuator with 3.5mm & 1/4" Jack Cables	
Interconnections	
Attenuation	100 V Line: -70 dB, -60 dB, -50 dB & -40 dB, Low Z Speaker: -50 dB, -40 dB, -30 dB & -20 dB
RF	
Input/s	100 V Line: 100 V AC, Low Z Speaker: 10 V AC
Physical	
Width	4.1 in. (105 mm)
Height	1.2 in. (31 mm)
Depth	2.4 in. (60 mm)
Shipping Weight	1.0 lbs. (0.5 kg)
Weight	.7 lbs. (.3 kg)