



Configuration:

LS-45-072 Listen Classic Level II Stationary RF System (72 MHz)

Product Overview:

For larger venues, the LS-45 Classic Level II Stationary RF System makes it easy to install and operate a compliant assistive listening setup in no time. Designed for use in larger venues, the LS-45 provides a coverage range of up to 1,500 ft (457.2 m) with 17 wide-band digital channels. The included LR-300 receivers are digitally tuned to ensure a strong, reliable signal at all times, and each receiver benefits from our Super Quiet Companding Technology that offers 20 dB less noise than competitors' receivers. The transmitter is compatible with nearly any audio source thanks to universal inputs, and the package includes everything needed to meet compliance requirements right away.

The LS-45 is available for the 72 MHz band only.

Highlights:

- Ensures public venues deliver an enriched listening experience while meeting new legislative requirements for assistive listening
- Superior audio quality 80 dB signal-to-noise ratio (SNR), setting the industry's sound quality standard
- · Offers 17 wide band 100% digital channels Listen receivers are digitally-tuned so the transmission won't drift
- Long transmission range ensures coverage for the entire venue

Includes:

One (1) LT-800-072-01 RF Transmitter (72 MHz)

One (1) LA-122 Universal Antenna Kit (72 MHz and 216 MHz)

One (1) LA-326 Universal Rack Mounting Kit

Four (4) LR-300-072 Portable Digital RF Receiver (72 MHz)

Four (4) LA-164 Ear Speaker

Two (2) Neck Loop

One (1) LPT-A107A-B Dual RCA to Dual RCA Cable 6.t ft. (2 m)

Four (4) LA-361 High Capacity AA Alkaline Batteries (2)

One (1) LA-304 Assistive Listening Notification Signage Kit

Product Specification: Listen Classic Level II Stationary RF System (72 MHz)	
Physical	
Shipping Weight	24.0 (10.3)