



**Configuration:**

- LS-47-072 Listen Premiere Level I Stationary RF System (72 MHz)
- LS-47-216 Listen Premiere Level I Stationary RF System (216 MHz)

**Product Overview:**

The LS-47-072 Premiere Level I system comes equipped with our LR-400 digital display receivers, which make it easier to monitor channel selection, battery level, and signal strength. Ideal for applications when assistive listening, single channel language interpretation, and personal use are desired. Venues will benefit from managing the LR-400 when locking on one channel is needed, but programming multiple channels are not or if the receiver channel is not changed regularly by the user. The included neck loops and signage ensures the system meets the minimum legislative requirements for venues with a capacity up to 100. Telescoping antenna gives smaller venues the option for using the transmitter within a 198 m (650 ft.) range.

**Highlights:**

- Ensures public venues deliver an enriched listening experience while meeting new legislative requirements for assistive listening
- Superior audio quality - 80 dB signal-to-noise ratio (SNR), setting the industry’s sound quality standard
- Offers 57 digital channels - Listen receivers are digitally-tuned so the transmission won’t drift

**Includes:**

- One (1) LT-800-072-01 RF Transmitter (72 MHz)
- One (1) LA-106 Telescoping Top Mounted Antenna (72 MHz)
- Four (4) LR-400-072 Portable Display RF Receiver (72 MHz)
- Four (4) LA-164 Ear Speaker
- Two (2) LA-166 Neck Loop
- One (1) LPT-A107-B Dual RCA to Dual RCA Cable 6.6 ft. (2 m)
- Four (4) LA-361 High Capacity AA Alkaline Batteries (2)
- One (1) LA-304 Assistive Listening Notification Signage Kit

Product Specification: Listen Premiere Level I Stationary RF System (72 MHz)	
Physical	
Shipping Weight	10.0 (4.5)