



Configuration:

LS-50-072 Listen Ultimate Level I Stationary RF System (72 MHz) LS-50-216 Listen Ultimate Level I Stationary RF System (216 MHz)

Product Overview:

The LS-50-072 Premiere Level I system comes equipped with our LR-500 digital display receivers, which make it easier to program, monitor channel selection, battery level, and signal strength. Ideal for applications when multi-language interpretation or a variety of audio sources need to be heard by a variety of listeners. Venues will benefit from managing the LR-500 when one receiver is used with multiple transmitters (audio sources) and users need the convenience of changing the channels themselves and programming of multiple channels is desired, so that users select only from the active channels. The included neck loops and signage ensures the system meets the minimum legislative requirements for veunes with a capacity up to 100. Telescoping antenna gives smaller venues the option for using the transmitter within a 198 m (650 ft.) range.

Highlights:

- Ensures public venues deliver an enriched listening experience while meeting new legislative requirements for assistive listening
- Superior audio quality 80 dB signal-to-noise ratio (SNR), setting the industry's sound quality standard
- · Offers 57digital channels Listen receivers are digitally-tuned so the transmission won't drift

Includes:

One (1) LT-800-072-01 RF Transmitter (72 MHz)

One (1) LA-106 Telescoping Top Mounted Antenna (72 MHz)

Four (4) LR-500-072 Portable Programmable Display RF Receiver (72 MHz)

Four (4) LA-164 Ear Speaker

Two (2) LA-166 Neck Loop

One (1) LPT-A107-B Dual RCA to Dual RCA Cable 6.6 ft. (2 m)

Four (4) LA-361 High Capacity AA Alkaline Batteries (2)

One (1) LA-304 Assistive Listening Notification Signage Kit

| Product Specification: Listen Ultimate Level I Stationary RF System (72 MHz) | |
|--|------------|
| Physical | |
| Shipping Weight | 10.0 (4.5) |