

FLURRY™ Z

Color Wash, Zoom + Eye Candy

Ring Effects + Motorized Zoom

Flurry™ Z is capable of producing bright, evenly dispersed light, and offers 3 zones (inner, middle, & outer rings) of LED control to pixel map its 19* 15W RGBW 4-in-1 LEDs. It also features fast and smooth 5° - 50° zoom for sharp beams, wide coverage, and everything in between.

Packed with Goodies

This incredible fixture is equipped with 16 preset single color + zone color combinations, and mind-blowing fade/pulse effects that make for serious eye-candy. Industry standard powerCON® connections, smooth 540/280° pan and tilt, and DMX 3-pin in/out jacks round out its list of features.

Luminous Intensity:

Beam	2.5-meters	5-meters	7.5-meters	10-meters
50° (lux)	2,166	512	276	182
5° (lux)	25,288	5,986	2,758	1,599
50° (fc)	201.2	47.6	25.6	16.9
5° (fc)	2,349.4	556.1	256.3	148.6



Main Features

- 19x 15W ultra-bright 4-in-1 RGBW LEDs
- Pan: 540°/ Tilt: 280° (8-16 Bit Resolution)
- 5 to 50-degree motorized zoom
- 16 static color presets + 10 color chase macros
- 0% - 100% electronic dimming
- Fast pan/tilt + optional invert for contrasting movements
- Built-in auto and sound active programs
- Fast fade & smooth fade dimming profiles
- Internal fan cooling system
- PowerCON® compatible power input/output
- Dual omega brackets with 1/4-turn fasteners



Optical

19* 15W ultra-bright 4-in-1 RGBW LEDs

5 to 50-degree motorized zoom

Narrow: 25,288 Lux @2.5M, 5,986 Lux @5M

Wide: 2,166 Lux @ 2.5M, 512 Lux @ 5M



Weight & Dimensions

12.2" L x 7.9" W x 15.8" H (31 x 20 x 40 cm)

17.5 lbs. (7.9 kg)



Control

Protocol: USITT DMX-512

8/15/23-channel DMX

4-button control panel with LCD display

3-pin DMX In/Out

DMX512, master/slave, auto, sound active



Power + Current

90-240VAC, 50-60 Hz

Power consumption: 230W, 2.94A, PF: .68

PowerCON™ compatible AC power In/Out connectors



Warranty

2-year limited warranty