



## LED-1003HDLX

This 9.7" flush mount monitor features the latest screen imaging technology for enhanced clarity and sharpness. With no front controls, this model is ideal for public areas.

### Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Durable metal case
- No front controls

### Related Products

- LED-1003HD: 9.7" Free-standing LCD monitor
- LED-1003HDX: Same model as LED-1003HD with no front controls
- LED-1003HDL: Same model as LED-1003HD in a flush mount kit

### Specifications

<b>Mount</b>	Flush Mount
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable Metal
<b>IR Remote Control</b>	Yes
<b>Native Aspect Ratio</b>	4:3
<b>Visible Screen Size (WH)</b>	7.8" x 5.9" / 198.1 x 149.9mm
<b>Resolution</b>	1024(H) x 768(V); displays 1080i/p
<b>Brightness Rating</b>	400 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED (30K)
<b>Dot Pitch</b>	0.192(H) x 0.192(V)mm
<b>Color Depth</b>	262,144
<b>Number of Pixels</b>	786,432
<b>Response Time</b>	20ms / 20ms (Rising/Falling)
<b>Audio Power / Speakers</b>	x2 Speakers
<b>Viewing Angle (L/R/T/B)</b>	89/89/89/89 degrees
<b>Installer's Cut Out</b>	9.25" x 7.67" / 235 x 195mm
<b>DSP</b>	3D Interlace comb filter, DNR, 4H filter
<b>Dimensions</b>	10.8" x 9.8" x 1.85" / 274.3 x 248 x 46.99mm
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Power Requirements</b>	12VDC; 1A; Negative Ground
<b>Power Consumption</b>	30 Watts (Max)
<b>HDMI</b>	x1 Input
<b>VGA</b>	x1 15-pin D-sub Input
<b>Composite</b>	x1 BNC Input; x1BNC Output
<b>Audio</b>	x1 RCA L/R Input; x1 3.5mm PC Input
<b>Power</b>	x1 2.1mm DC Input
<b>Weight</b>	Net: 4 lbs / 1.81 kg; Gross: 6.25 lbs / 2.8 kg

Specifications subject to change.