

S4.10 Series UHF Wireless Microphone System



S4.10 Series Multi-channel plug and play system

The Trantec S4.10 Series is designed to make multi channel wireless as simple as possible.

The system is encased in a sturdy yet compact metal frame. It can be used with a wide range of microphones, or musical instruments making it the perfect solution for amateur and semi professional musicians and theatre performers.

S4.10-RXA-AMRM3QU	 Up to 16 selectable frequencies (Up to 16 Simultaneous channels) Frequency scan function IR Sync - Infrared auto channel setup Numerical LED display Adjustable output level Indication of transmitter's battery life Selectable from desk-top receiver
S4.10-HDX-AMWM3QU	 Handheld transmitter with dynamic cardioid microphone unit 1 AA battery provides up to 10 hours of continuous use IR Sync - Infrared auto channel setup Adjustable microphone sensitivity Numerical LED display Battery life indicator
S4. 10-LTX-AMWM3QU	 Beltpack transmitter works with any Trantec microphone or alternatively a musical instrument cable 1 AA battery provides up to 10 hours of continuous use IR Sync - Infrared auto channel setup Integral switch for selection between instrument and microphone Numerical LED display Adjustable sensitivity Battery life indicator

SPECIFICATIONS

54	10	Ser	ies
<u> </u>		001	

Receiver	S4.10-RXA-AMRM3QU UHF Wireless Receiver
Diversity Reception	Antenna Diversity
Frequency Range	506 - 538 MHz, UHF
Channel Selectable	Up to 16 channels (Region dependent)
Sensitivity	10uV at 45 dBA S/N
Squelch (SQ)	Tone SQ, Carrier SQ, Noise SQ
Audio Frequency Response	50 Hz - 15k Hz
Audio Output Level	Balanced (XLR socket) : -16 dBu
(Maximum)	Unbalanced (1/4" jack socket) : 10 dBu
Power Supply	11-18 VDC 300 mA
Dimensions	215 (W) x 39 (H) x 102 (D) mm
	(excluding antenna and BNC)
Weight	480g

Available SystemsS4.10-HD-AM RM3QU...wireless system with
dynamic handheld micS4.10-L-AM RM3QU...wireless system with
body pack & lavalierS4.10-HDX-AMWM3QU...handheld wireless mic
S4.10-LTX-AMWM3QUS4.10-RXA-AMRM3QUBandFrequencyM506 - 538 MHz, UHF

M	506 - 538 MHz, UHF
Version	AC Adapter
(US)	120 V AC, 50Hz

TOA Canada Corporation Tel: 1-800-263-7369 • Fax: 1-800-463-3569 sales@toacanada.com • www.TOAcanada.com



