

PROLOOP FSM plus

Magnetic Field Strength Measuring Device



The new PROLOOP FSM plus is a measuring device that measures the magnetic field strength of induction loop systems according to IEC 60118-4:2006 and BS 6083, Para. 4. The device is designed for professional use and delivers reliable RMS values on the output level, response frequency, AGC function (Automatic Gain Control), distortion and background noise in the tested induction loop. In addition, it enables the user to make an acoustic evaluation of the sound via earphones.

- Conforms to IEC 60118-4: 2006 standard
- Adjustment possibilities for two test ranges:
 - background noise
 - field strength
- RMS-measuring range calibrated to 400mA/m = 0dB
- Multi-colored LEDs for excellent legibility
- LED-scale with 1dB resolution
- 3.5 mm stereo headphone jack with volume control
- Handy, light-weight, rugged chassis
- Switchable A weighted filter

| | |
|-------------------------|--|
| True RMS: | 125 ms average time |
| Measuring range: | +6 dB -40 dB (0 dB = 400mA/m) |
| Power supply: | 2x 1.5V AA batteries |
| Display: | LED Battery status control |
| Field strength: | LED-Scale (1dB resolution) |
| Output: | 3.5 mm stereo headphone jack with volume control |
| Dimensions: | 3.3" x 5" x 1.4" (83 x 126 x 35 mm) |
| Weight: | 6.0 oz. (170 g) (incl. batteries) |
| Warranty: | 2 years |

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Domestic Sales

Williams AV
 10300 Valley View Rd
 Eden Prairie, MN 55344
 Ph: 800-328-6190 / 952-943-2252
 FAX: 952-943-2174
 Email: info@williamsav.com
 Web: www.williamsav.com

International Sales

International Sales Department
 Williams AV
 10300 Valley View Rd
 Eden Prairie, MN 55344 USA
 Phone: +1 952 943 2252
 Fax: +1 952 943 2174
 Email: info@williamsav.com
 Web: www.williamsav.com

WILLIAMS AV
 info@williamsav.com / www.williamsav.com
 800-843-3544 / INTL: +1-952-943-2252