

Production Intercom • High Noise Environments • Live Sound Stage • Factory Tours • Military Training

PLW 014

POWER LOOP WIRE 14 GA



Power loop wire, 14 ga, 500 ft (152.4 m) spool, black.

Industry Approvals

- CSA Spec. C22.2, No. 127
- UL Spec. AWM Style 1015, 1019, 1020, 1230, 1284, 1032, 1283, 1232, 1028
- CSA LL90458
- UL E30398
- Meets material content restrictions of the RoHS-2 Directive

PLW 014

Wire Type	Stranded bare copper
Insulation Type	Thermoplastic insulation
Length	500ft (152.4 m)
Spool Dimensions	6.5"W
Spool Weight	9.8 lbs
Color/Material	Black
Max. Temperature Exposure	105°C Dry
Rating	600 Volt
Conductor Size (AWG)	14
Number of Strands	41
Nominal Insulation Thickness	0.030 in. (0.76 mm)
Nominal Overall Diameter	0.136 in (3.45 mm)
Net Weight	4.2 kg (9.15 lbs)
Approvals	RoHS

Domestic Sales

Williams AV
 10300 Valley View Rd
 Eden Prairie, MN 55344
 Ph: 800-328-6190 / 952-943-2252
 FAX: 952-943-2174
 Email: info@williamsav.com
 Web: www.williamsav.com

International Sales

International Sales Department
 Williams AV
 10300 Valley View Rd
 Eden Prairie, MN 55344 USA
 Phone: +1 952 943 2252
 Fax: +1 952 943 2174
 Email: info@williamsav.com
 Web: www.williamsav.com

WILLIAMS AV

info@williamsav.com / www.williamsav.com
 800-843-3544 / INTL: +1-952-943-2252