

## Install

# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

- 3 way compact wall mount loudspeaker for multi-zone music and AV systems
- 25 mm titanium diaphragm high frequency unit delivers exceptional clarity and articulation throughout the high frequency range
- 2 x 6" bass drivers provide exceptional low frequency performance
- 80 Watts continuous, 320 Watts peak power handling delivers exceptional dynamics and realism
- Highly efficient 92 dB/Watt sensitivity
- WideBand tweeter technology to enhance reproduction of wide band digital audio formats
- Robust construction and performance allows use within commercial environments
- Ideal for paging systems, boardrooms, offices, business music systems, reception rooms, houses of worship, retail outlets, shopping malls and bars
- Weather resistant steel mesh grille to protect driver
- Semi matt white finish fits unobtrusively in any environment
- Both baffle and grille may be painted to match décor
- Innovative self-aligning clamping system for easy installation into standard stud partition wall

Designed to excel in a wide variety of sound reinforcement applications, the full range iW 62DS-WH is a compact 320-Watt wall mount loudspeaker that provides inspiring acoustic performance with exceptional clarity and articulation. The iW 62DS-WH is ideally suited for paging systems, boardrooms, offices, business music systems, reception rooms, houses of worship, retail outlets, shopping malls and bars.



## Superb Performance

iW 62DS-WH's design comprises dual 150 mm (6.00") bass drivers with a 25 mm (1.00") titanium diaphragm high frequency unit mounted in an enclosure that is robust enough for commercial applications. This configuration handles up to 320 Watts to deliver exceptional dynamics, realism, and enhanced intelligibility, all in a compact and highly efficient system that is well-suited to a wide range of amplifier options – including entry level amplifiers.

## Install

# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

- Bi-wireable to improve signal transmission and integrity
- Driver ground connection minimises RF interference Dynamic high frequency protection
- Tannoy - Over 90 years of British sound heritage and innovation
- 10-Year Warranty Program\*
- Designed and engineered in the U.K.

## Attractive & Easy to Install

The semi matt white, weather resistant grille and enclosure can be painted to match any décor, and features an innovative self-aligning clamping system for easy installation into standard stud partition walls.



## You Are Covered


We always strive to provide the best possible Customer Experience. Our products are made in our own Music Tribe factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world. As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous Warranty program.

Install


# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

## Frequency Response Sensitivity 1 W / 1 m




## Impedance




# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

## Horizontal and Vertical Beamwidth



## Directivity Index and Factor









Install

# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

## Horizontal Polar Plots









Install

# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

## Vertical Polar Plots




Install


# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)


## Dimensions




BOTTOM



FRONT



SIDES



BACK

## Install

# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

## Technical Specifications

### Performance

Frequency response ( $\pm 3$ dB)	70 Hz - 20 kHz
Frequency response (-10 dB)	34 Hz - 20 kHz
Low frequency alignment (-6 dB)	34 Hz
Power handling (see note 1)	80 W continuous, 320 W peak
Recommended amplifier power	20 - 160 W @ 8 $\Omega$
System sensitivity	92 dB (2.83 V @ 1 m)
Nominal impedance	8 $\Omega$
Rated maximum SPL	111 dB continuous, 117 dB peak
Crossover	Passive, 2nd order LF, 1st and 2nd order band-pass mid, 2nd order HF
Crossover point	500 Hz, 1.5 kHz
Crossover HF adjustment	$\pm 1.5$ dB

### Transducers

High frequency	25 mm (1") 25-micron titanium dome, neodymium magnet system
Low frequency	2 x 165 mm (6.5") multifibre paper pulp cone
Wiring	Positive LF, positive HF, negative LF, negative HF, ground

### Physical

Dimensions (H x W x D)	473.5 x 227 x 92 mm (18.6 x 8.9 x 3.6")
Mounting depth	99 mm (3.9")
Net weight	4.2 kg (9.3 lb)
Construction	Baffle panel: moulded UV Resistant ABS, Clamps: moulded polycarbonate
Finish	White, paintable
Grille	Powder coated perforated steel

#### Notes:

1. Long-term power handling capacity as defined in IEC standard IEC268-5
2. Averaged over specified bandwidth for half space environment. For anechoic conditions the figure is to be decreased by 3 dB
3.  $\pm 3$  dB, measured at 1 metre in anechoic chamber in a critically tuned enclosure.
4. Remove links when bi-amping or bi-wiring
5. Remove links in stereo operation



# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)

## Architecture & Engineering Specifications

The in-wall speaker shall consist of two 165 mm (6.50") bass/mid units and one 25 mm (1.00") high frequency driver mounted in an injection moulded front baffle manufactured from UV/weather resistant UL94V-0 ABS material. The three-way system shall incorporate an optimised low loss crossover network. The wiring terminals shall be screw terminal connectors.

Performance of the in-wall speaker shall meet or exceed the following criteria: The system shall have a coverage angle of 130 x 90 degrees (1 kHz to 6 kHz). Frequency response measured on axis shall be 34 Hz - 20 kHz (-10 dB from rated sensitivity, measured in an IEC baffle in an anechoic chamber) with no equalization. Sensitivity shall be 92 dB (1 W @ 1 m). Long term power handling capacity as defined in EIA-426B test shall be 80 W, recommended amplifier power 160 W @ 8 Ohms. The nominal system impedance shall be 8 Ohms.


A weather resistant perforated steel grille covers the transducer. Both the grille and baffle shall be paintable. The system shall not exceed the following dimensions: 473.50 x 227 x 92 or 18.6 x 8.9 x 3.6 (H x W x D). Hole cut out size shall be 426.10 x 187.6mm (16.76 x 7.39")

The [Tannoy](#) in-wall speaker system shall be the.....iw62 DS-WH.

Install

# iW 62DS-WH


3 Way 6" In-Wall Loudspeaker (White)



Install

# iW 62DS-WH


3 Way 6" In-Wall Loudspeaker (White)



Install

# iW 62DS-WH


3 Way 6" In-Wall Loudspeaker (White)



## Install

# iW 62DS-WH

3 Way 6" In-Wall Loudspeaker (White)



For service, support or more information contact the Tannoy location nearest you:

**Europe**  
**Music Tribe Brands UK Ltd.**  
Tel: +44156 273 2290  
Email: CARECrea@musictribe.com  
CAREEnte@musictribe.com  
CARELife@musictribe.com

**USA/Canada**  
**Music Tribe Commercial NV Inc.**  
Tel: +1 702 800 8290  
Email: CARECrea@musictribe.com  
CAREEnte@musictribe.com  
CARELife@musictribe.com

**Japan**  
**Music Tribe Services JP K.K.**  
Tel: +81 3 6231 0453  
Email: CARECrea@musictribe.com  
CAREEnte@musictribe.com  
CARELife@musictribe.com

Music Tribe accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. Midas, Klark Teknik, Lab Gruppen, Lake, Tannoy, Turbosound, TC Electronic, TC Helicon, Behringer, Bugera and Coolaudio are trademarks or registered trademarks of Music Tribe Global Brands Ltd. © Music Tribe Global Brands Ltd. 2019 All rights reserved.

# TANNOY