LOUDSPEAKER ASSEMBLIES



8C5PAX/TBLU

LOUDSPEAKER AND TRANSFORMER

8" O.D. Loudspeaker with a 5 oz. magnet and a 5W-25/70V Transformer

GENERAL DESCRIPTION

The **8C5PAX/TBLU** consists of an 8C5PAX - 8" O.D. dual cone loudspeaker with a 5 oz. magnet, and a 5W-25/70V transformer. Loudspeaker frame is finished in black powder coat.

INTENDED USE - Indoor Environment

Program Material | Signal tones, voice, and music

AUDIO SPECIFICATIONS


92 dB SPL, 1W/1M Average Sensitivity **Loudspeaker Power Rating** 12W RMS, EIA 426A Standard **Maximum Power Rating** 15W @ 8 Ohms Calculated Output 99 dB SPL, 5W/1M Magnet Type & Weight | BeFe Ceramic, 5 oz. Nominal Frequency Response 65 Hz - 17 kHz EIA 426A Standard Nominal Coverage Angle 100° Included Angle, -6 dB / 2 kHz, Half space **Audio Connection** 7" Color-Coded Leads Wattage Taps | 0.31W, 0.63W, 1.25W, 2.5W, 5W


RECOMMENDED QUAM COMPONENTS

Baffles Round: BR8-2WS, BR8B, BR8VP, BR8W, BR8WS

Square : BS8VP, BS8VPS, BS8W, BS8WS







Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the Specs and Diagrams section at: www.QuamSpeakers.com





