



VANDAL RESISTANT

DTS2

INTERCOM STATION

Desktop Intercom Station, Flush Microphone

GENERAL DESCRIPTION

The **DTS2** is a vandal resistant, desktop intercom station consisting of a 30C25Z80T - 3" square frame loudspeaker with a 2.35 oz. ceramic magnet and a moisture resistant cone - a push-to-talk (PTT) button and an integrated omni-directional electret microphone. Stainless steel faceplate with three (3) interwoven, steel security screens mounted between the loudspeaker. Console finish is black powder coat. Tamper resistant, 6-32 x 1" 'pin-in-torx' hardware included.

INTENDED USE - Indoor Environment

Program Material | Signal Tones and Voice

Simplex, two-way communication using PTT microphone and internal, 'never full off' volume controlled, moisture resistant loudspeaker. The loudspeaker is internally configured for either 8 Ohm or 25V systems. 3.5 mm output jack allows use of a low impedance headset (not supplied), by-passing the loudspeaker function. Pre-drilled holes in the base allow for bolt-down applications.



AUDIO SPECIFICATIONS

SPEAKER	
Average Sensitivity	87 dB SPL, 1W/1M
Magnet Type & Weight	BeFe Ceramic, 2.35 oz. Nominal
Frequency Response	150 Hz - 10 kHz EIA 426A Standard
MICROPHONE	
Sensitivity	-51 dBV/Pa + 4dB (0 dB = 1V/Pa, 1kHz)
Impedance	600 Ohms Nominal
Frequency Response	180 Hz - 12 kHz + 3 dB
Supply Voltage	1.5V, 0.5mA Maximum Draw

ELECTRICAL SPECIFICATIONS

Volume Control	-15 dB Maximum Attenuation
Headset Jack	Two (2) 3.5 mm, mono input/output. Disconnects 'never full off' loudspeaker output when activated

