



## H 200 2-Channel IR Wireless Receiver

Two-channel or stereo stethophone receiver with BA 90 NIMH rechargeable battery. Lightweight, easy to use and can be worn comfortably for long periods of time

### Features—Benefits

- Lightweight—can be worn for long periods of time
- Built in on/off switch, volume control, and channel selector—more flexibility
- 18 Hz–18 kHz frequency response

### Technical Data

Infrared wavelength	950 NM
Modulation	FM
Carrier frequency	95 kHz (channel 1) 250 kHz (channel 2)
Frequency response	30–18,000 Hz
Distortion	Typ. 1%
Signal-to-noise ratio	60 dB (A)
Operating time	7 hours
Volume	118 dB, SPL
Weight	1.5 oz

### Product Variants

Single channel receiver	RI 100A/-J
Single channel receiver, 95 kHz	HDI 91-P1
Single channel receiver, 250 kHz	HDI 91-P2
Two-channel stereo receiver	HDI 92-P

### Supplied Accessories

---

(1) Receiver	H 200
(1) Rechargeable battery	BA 90

### Optional Accessories

---

Latex replacement ear cushions	EP405-L
Transparent latex replacement ear cushions	EP405-L-TRA
Foam replacement ear cushions	EP 405-F

#### Recommended chargers

Charger for one BA 90	L90-120
Charger for 10 BA 90's	L 92-10/NT
Charger for 20 BA 90's	L 92-20/NT
Carrying case and charger for (20) batteries	HC101

### Product Compatibility

---

SI20 Transmitter  
SI20-R Transmitter  
S220 Portable System  
SZI1029T-120 Single channel transmitter (switchable)