IP Joystick (GEN3)

PTZOptics

4D IP Joystick Controller

Compatibility

- VISCA over IP protocol
- All PTZOptics Cameras
- Other VISCA over IP cameras

What's in the box?

- Four-Axis Joystick
- 12V DC Power Supply
- User Manual


Main Features

- Durable Metal Housing
- VISCA over IP protocol
- Auto-Search network
- Real time status display
- Pan, Tilt, Zoom Control
- Pan & Tilt Speed Control
- PoE (802.3af)
- Assignable Control Port

Auto-search your network for VISCA over IP compatible devices. Use any pan, tilt & zoom controls for any or multiple VISCA over IP protocol cameras! Controls pan, tilt & zoom with variable speeds. For best results, pair with a PTZOptics camera.

Model Number: PT-JOY-G3





- 1. LCD Display

 Menu options displayed here
- **2. Joystick** Three-axis joystick controller
- Camera Quick Select
 Quickly swap between 6
 cameras
- 4. PTZ & Preset Control
 Adjust PTZ speed, set & call
 presets, & modify OSD menu
- Numeric Keys
 Numeric keys for presets, changing parameters, & more
- 6. Camera Image Control
 Adjust Iris, auto focus, & auto
 exposure
- 7. Focus Control Keys
 Focus+, Focus-, Auto Focus
 on/off
- 8. VISCA Connections
 VISCA connections are not supported on this model
- 9. RJ45 Connection Used for IP and PoE (802.3af) Connection
- **10.** Power Connection 12V DC Power Connection

Key Technical Specifications	
Connections	RJ45 Network Connection
Maximum Cameras	Control up to 253 Cameras
Maximum Distance	328 Ft. (100 meters) cable length to nearest LAN switch
Other.	-
Warranty	1 Year

Operation Specifications	
Power	5W (12VDC Voltage) or PoE (802.3af)
Working Temp	32° F ~ 131° F (0° ~ 55° C)
Working	10 ~ 90% (non-condensation)
Weight	3.3 lbs 1.5 kg
Dimensions (in.)	12.6W x 7.1H x 4.3D
Dimensions	320W x 181H x 110D