

livesound

portablesound

installedsound

# TCX-18B bandpass subwoofer

## Features

- Bandpass loading
- Pole mount socket
- Internal rigging points
- Speakon NL4 and barrier strip connectors

## Applications

- Mobile DJ
- Corporate / industrial
- House of Worship
- Theatre
- Live music venues




**The TCX-18B is a compact sub-bass loudspeaker consisting of a 18" low frequency driver in a bandpass-loaded enclosure designed for extended low frequency response.**

When permanently installed the cabinet presents a discreet appearance, while for portable use the pole mount socket allows TCX series two-way loudspeakers to be mounted on a straight speaker pole above the subwoofer. The cabinet is finished as standard in black textured paint (or optional white), and includes internal threaded rigging points that allow it to be suspended in permanent installations using M10 eyebolts. A rear panel provides two Speakon NL4 connectors wired in parallel with a 4-way barrier strip connector. When used with optional Turbosound Loudspeaker Management Systems, TCX loudspeakers can be controlled and monitored over a BVNet network using TurboDrive™ control software.

## Compact series

Frequency Response




**TURBOSOUND Ltd**  
Star Road  
Partridge Green  
West Sussex  
RH13 8RY  
United Kingdom

t: +44 (0)1403 711447  
f: +44 (0)1403 710155  
e: techsupport@turbosound.com  
w: [www.turbosound.com](http://www.turbosound.com)

# TCX-18B

bandpass subwoofer

<b>DIMENSIONS (HxWxD)</b>	660mm x 560mm x 660mm (26" x 22" x 26")
<b>NET WEIGHT</b>	38.5kg (84.7 lbs)
<b>COMPONENTS</b>	1 x 18" (457mm) LF driver
<b>FREQUENCY RESPONSE</b>	35Hz - 150Hz $\pm$ 3dB, 25Hz - 170Hz $\pm$ 10dB
<b>POWER HANDLING</b>	1000 watts continuous, 2000 watts program
<b>SENSITIVITY</b>	97dB, 1w @ 1m
<b>MAXIMUM SPL</b>	127dB continuous, 133dB peak
<b>NOMINAL IMPEDANCE</b>	8 ohms
<b>CONSTRUCTION</b>	15mm (5/8") birch plywood, finished in black semi-matt textured paint
<b>CONNECTORS</b>	(2) Speakon NL4MP, wired pin 1+: positive, pin 1- : negative, pins 2+ and 2- N/C (1) 4-way barrier strip connector
<b>FLYING HARDWARE</b>	(8) M10 internal rigging points for eyebolts
<b>OPTIONS</b>	White semi-matt textured paint
<b>SPARES AND ACCESSORIES</b>	LS-1816 18" LF loudspeaker RC-1816 Recone kit PA-90 Speaker pole 90cm PA-100 Speaker pole 100cm
<b>MORE INFO</b>	More information can be found on our website: <a href="http://www.turbosound.com">www.turbosound.com</a>



### Limited Warranty

Every Turbosound loudspeaker product is warranted to the original end-user purchaser and all subsequent owners for a period of two (2) years for loudspeaker products, or one (1) year for electronics products, from the original date of purchase. Warranty coverage includes defects in materials and workmanship. It does not include:

- damage caused by accident, misuse, abuse, neglect or modification by any other person other than an authorised Turbosound representative,
- damage caused by overdriving, use with unsuitable amplifiers or amplifier failure,
- damage caused by failure to operate the product in accordance with the instructions contained in the user's manual,
- damage occurring during shipment in transit,
- claims based upon any misrepresentations by the seller,
- products which do not have the original components as specified in the product engineering information,
- products on which the serial number has been removed or defaced.

Should any fault develop with a component of your Turbosound system, please return the product, freight pre-paid, in its original packing carton, along with proof of purchase such as the original bill of sale, and a description of the suspected fault, to your local authorised Turbosound representative. The product serial number must be quoted in all correspondence relating to the claim. Insurance is recommended as Turbosound or its representatives are not liable for loss or damage in transit.