

# TOURNADO

IP W-DMX™

## 12\* 15W LEDs, IP65 Rated + Wireless W-DMX

The Tournado™ IP W-DMX is a tough IP65 rated fixture featuring super bright RGBAW+UV color mixing thanks to its installed 12x 15W 6-in-1 LEDs with advanced 25° optics. It has all the same advantages as the TOURnado™ IP EXA, but with the addition of a built-in W-DMX™ receiver to provide ultra-stable wireless communication.

It sports a convection cooled cast aluminum housing with a tempered glass lens, watertight internal gaskets, and weatherproof power and data cable in/out connections. Users can run any of its impressive built-in programs individually or all together in auto run mode with speed control, fade, flash, or perform full RGBAW+UV color mixing with or without DMX control.

The built-in W-DMX™ receiver works seamlessly with any W-DMX™ product and provides ultra-stable wireless communication for more than 500 meters (line-of-sight)!

The TOURnado™ IP W-DMX offer an easy-to-use 4-button control panel with an LED display. You have total control including master/slave settings, 5 auto modes, custom programs (up to 3\* 20 scene programs), fade, strobe, manual color adjustments, multiple user-selectable 32-bit dimming modes and more.

And as course, TOURnado™ IP W-DMX fixtures are backed by Blizzard's 2-year warranty!



**IP65**

SUITABLE FOR OUTDOOR USE

### Main Features

- RGBAW+UV color mixing via 12x 15W 6-in-1 LEDs
- 2.4Ghz built-in wireless W-DMX™ receiver
- LED control panel with 4 touch sensitive buttons
- Super-sharp 25° beam angle
- Variable electronic dimming & strobe
- Built-in color & chase macros via DMX
- Virtual color wheel effect
- Built-in automated programs via master/slave
- User selectable 4/5/6/7/9/12-channel DMX modes
- Convection cooled cast aluminum housing
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current LED driver
- IP rated locking power and 3-pin DMX connections
- Dimensions: 10.7x5.7x12.1 inches (27x14.4x40.7 cm)
- Weight: 11.5 lbs (5.2 kg)



#### Optical

Light Source: 12\* high output 15-watt RGBAW+UV LEDs

Beam Angle: 25°

Flicker-free LED

Luminous Intensity:  
13,700 Lux @ 1m | 3,900 Lux @ 2m



#### Wireless Receiver

Transmission band:  
2.4Ghz ISM (2.4-2.525Ghz)

Channels: 512

Receiver sensitivity:  
-94dBm



#### Control

Protocol: USITT DMX-512

4/5/6/7/9/12-channel DMX modes

Standalone, master/slave, DMX, auto modes

IP65 Seetronic 3-pin DMX input/output

4-button LED control menu display



#### Power + Current

100-264VAC, 47-63 Hz

Power Consumption:  
100W, 1.35A, PF: .6



#### Warranty + Certifications

2-year limited warranty, does not cover malfunction caused by damage to LEDs