# artec 300 series



# **ARTEC-312.64**



#### **DESCRIPTION**

The ARTEC-312.64 is a compact 2-way full-range loudspeaker system comprised of one 12" low frequency transducer and one M-34 compression driver with titanium diaphragm. The rotatable waveguide provides 60° x 40° coverage and allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration and at the same time, permits close-packed horizontal or vertical arrays.

The cabinet is fitted with M10 threaded suspension points. Four VESA75/VESA100 standard threaded mounting points on the rear of the cabinet provide a secure fixing point for DAS mounting brackets.

#### **KEY FEATURES**

- ·1 x 12MI low frequency loudspeaker, 2.5" VCD
- ·1 x M-34 compression driver
- · Rotatable 60° x 40° horn
- · Vertical or horizontal positioning
- · Optional AXU-AR312 U-Bracket
- M-10 rigging points

#### **APPLICATIONS**

- $\cdot$  A/V systems and corporate events
- · Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

#### **SPECIFICATIONS**

Performance		
Frequency Range (-10 dB)	50 Hz - 20 kHz	
Horizontal Coverage (-6 dB)	60°	
Vertical Coverage	40°	
Nominal Impedance	8 ohms	
RMS Power Handling	300 W	
Peak Power Handling	1200 W	
On-axis Sensitivity 1W/I m	96 dB SPL	
Maximum Peak SPL at 1 m	127 dB	
Recommended Amplifier	PA-1500	
Recommended Processor	DSP-226	
Connectors		
Audio Input Connector	Covered Barrier Strip Terminals	
Audio Output Connector	Covered Barrier Strip Terminals	
Enclosure		
Enclosure Construction	Birch Plywood	
Enclosure Geometry	Trapezoidal	
Rigging	M10 Rigging Points	
Finish	ISO-flex Paint	
Color	Black	
Depth	375 mm (14,8 in)	
Dimensions ( H x W x D )	615 x 385 x 375 mm 24,2 x 15,2 x 14,8 in	
Net Weight	18,5 kg ( 40,8 lb )	



### Components

Shipping Weight

LF Driver	12MI	
HF Driver	M-34	
Horn/Waveguide	BC-614	
Shipping		
Carton Dimensions ( H x W x D )	710 x 450 x 450 mm 28,0 x 17,7 x 17,7 in	

20,4 kg ( 44,9 lb )

# **ORDERING INFORMATION**

Performance		
Model	Description	P/N
System		
ARTEC-312.64	2-way Passive Point Source	10423821
Replacement Parts		
12MI	Cone Transducer	10214310
BC-614	Horn	30006443
F-AR315	Filter	30006593
GM-12MI	Recone Kit	20208290
GM-M34	Diaphragm	20205060
LAMP-F-21	Lamp	30000535
M-34	Compression Driver	10207080
Accessories		
ANL-2	Rigging Accessories	10101020
AX-SPG1	Installation & Stacking Acc.	10105050
AXC-AT	Installation & Stacking Acc.	10104310
AXR-AR5	Installation & Stacking Acc.	10104870
AXU-AR312	Installation & Stacking Acc.	10105090

## **DIMENSIONS**









