

4K UHD Home Theater & Gaming Projector UHD30





Stunning 4K UHD and outstanding gaming smoothness











Up to 15,000 hour lamp life reduces overall cost of ownership

Blu-ray 3D compatible



4KULTRA HD













Embrace 4K UHD on a huge screen with the 3,400 lumens Optoma UHD30 projector. Capable of projecting images up to 302-inches, the UHD30 delivers incredible details and vibrant colors that transform your home into a home cinema.

Gamers can take advantage of the ultrafast 1080p 240 Hz refresh rate for blur-free visuals with outstanding smoothness. Combining the blur-busting refresh rate with Enhanced Gaming Mode results in 16ms response time, or 25ms at 4K UHD, for a competitive gaming advantage.

HDMI 2.0 with HDCP 2.2 support ensures connectivity to the latest 4K UHD devices while a 12V trigger enables control of motorized screens. Up to 15,000-hour lamp life delivers many years of use with minimal maintenance when using Dynamic mode.

CONNECTIVITY (May require optional accessories)









OPTICAL/TECHNICAL SPECIFICATIONS

Texas Instruments™ 0.47" DMD
RGBWRGBW 8 segment color wheel
4K UHD (3840 x 2160) @ 60Hz with XPR Technology
4K UHD (3840 x 2160) @ 60 Hz 1080p (1920 x 1080) @ 240 Hz
3,400 ANSI lumens
Up to 500,000:1 with Dynamic Black
REC.709 color gamut provides rich accurate color based on the HDTV broadcast specification and used with all non-HDR content DCI-P3 wide color gamut is the equivalent to color in the CIE 1931 color space, resulting in vivid colors
HDR10 & HLG compatible (REC.2020) Picture Modes: Normal, Bright, Detail, Film HDR SIM (simulate HDR effect with non-HDR content)
Upscales WXGA, 720p, 1080p, WUXGA, 1440p resolutions and frame rates up to 4K UHD (3840x2160), 60 Hz
UltraDetail Technology enhances image quality by improving image depth and clarity
4K UHD (3840 x 2160) @30Hz YUV 4:4:4 (8bit, 10bit, 12bit), YUV 4:2:2 (8bit, 10bit, 12bit), YUV 4:2:0 (8bit, 10bit, 12bit) 4K UHD (3840x2160) @60Hz YUV 4:4:4 (8bit), YUV 4:2:2 (8bit), YUV 4:2:0 (8bit, 10bit, 12bit)
4K UHD (3840x 2160) @ 60 Hz: 25.8ms 1080p (1920 x 1080) @ 60 Hz: 23.8ms 1080p (1920 x 1080) @ 120 Hz: 18.2ms 1080p (1920 x 1080) @ 240 Hz: 15.7ms
4000/10,000/15,000 (Bright/ECO/Dynamic)
Front, rear, ceiling mount, table top
NA
±40°
80%
105% ±5%
16:9 (native), 4:3 and LBX compatible
1.50 - 1.66 (with tolerance ±3%)
4' - 49' (without zoom)
34.1" - 302.4
F=1.94 ~ 2.23, f=12.81 ~ 16.74 mm manual focus
1.1x
0.8 - 2.0
5W speaker
26dB
Full function home remote control
41-104°F (5-40°C), 85% max humidity
AC input 100-240V, 50-60Hz, auto-switching
315W typical (Bright), 347W max (Bright), 225W typical (ECO), 248W max (ECO)
Operating temp @ sea level to 10000 feet = 23C (max); must manually switch to high altitude mode @ 5000 feet & above (using OSD)

COMPATIBILITY SPECIFICATIONS

Computer Compatibility	4K UHD 2160p, WUXGA, HDTV 1080p, UXGA, SXGA, WXGA+, WXGA (1366x768), WXGA, HDTV (720p), XGA, SVGA, VGA, PC and Mac compatible
Video Compatibility	4K UHD 2160p (24/50/60Hz), 1080p (24/50/60Hz), 1080i (50/60Hz), 720p (50/60Hz), 480i/p, 576i/p
HDR Source Compatibility	Ultra HD Blu-Ray player, 4K UHD streaming media device (Roku 4K Ultra), Xbox One S / One X (Ultra HD Blu-ray, 4K media streaming & HDR gaming) and PS4 Pro (4K UHD media streaming and 4K UHD HDR gaming only)
3D Compatibility [†]	Blu-ray 3D / Frame-pack: 1080p24, 720p50 / 60 (per eye) Sequential: 1080p24/30 (per eye)
Vertical Scan Rate	24Hz to 120Hz
Horizontal Scan Rate	31.000 to 135.000KHz
User Controls	Complete on-screen menu adjustment in 27 languages
I/O Connection Ports	HDMI 2.0 (w/ HDCP 2.2, MHL 2.1), HDMI 1.4a, VGA-in, audio-in (3.5mm), audio-out, S/PDIF out (optical), USB 2.0 (service port), USB power (5V, 1.5A), RS-232C, 12V Trigger
Loop Through (Audio)	Audio passthrough from HDMI to 3.5mm audio out and optical S/ PDIF out (2 channels)

^{*}Light source life is dependent upon many factors, including brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.




1. USB (service) 5. HDMI 1.4a 2.RS-232C 6. USB Power 3. VGA 7. Audio-In 4. HDMI 2.0 8. Optical S/PDIF

9. Audio-In 10. Audio-Out

11. AC Power

12. Kensington™ Lock



PHYSICAL SPECIFICATIONS

Security	Kensington® lock port, password (OSD)
Weight	8.6lbs.
Dimensions (W x H x D)	12.4" x 4.6" x 10.6"

Warranty

1-Year parts and labor limited warranty on the projector, 90 days lamp warranty

What's in the Box

UHD30, AC power cord, remote control, batteries for remote and quick start user manual

Accessories

Lamp (replacement): BL-FP240E Remote (replacement): BR-3003B Universal mount: OCM815W, OCM818W-RU

UPC 796435 81 363 5



Optoma.com

Copyright © 2020 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments". All other trademarks are the property of their respective owners. All specifications subject to change at any time. 06192020

[†]3D content can be viewed with DLP Link active shutter 3D glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.