# CDA-2

# **Computer Distribution Amplifiers**





The CDA-2 is a computer video distribution amplifier. It takes the input signal from the video card of a computer and splits it to be used by a projector and a monitor. This unit not only splits the signal it also buffers it to ensure absolute signal integrity at the receiving device (projector or monitor). With 300 MHz of bandwidth, the CDA-2 can support up to a QXGA (2048 x 1536 @ 60Hz) computer video signal approximately 50 feet using high resolution cable.

#### **FEATURES:**

- Compatible with LCD panels, projectors and monitors
- Two outputs
- Metal case provides superior shielding
- HD 15-pin 5 ft. male-to-male monitor cable included
- 300 MHz video bandwidth
- Drive outputs approximately 50 feet
- · Individually buffered outputs
- UL and CSA approved external power supply (wall plug-in)
- ID bits passed through to output one (permits monitor to determine video resolution)
- · Locking power connector

Video Inputs:

Number/type 1 RGB + Sync
Connectors 15 pin HD female
Level (nominal) Analog 0.7V p-p
Level (maximum) 2V p-p
Impedance 75 ohms

Horizontal frequency 15 kHz - 200 kHz Vertical frequency 30 Hz - 150 Hz

Unity

75 ohms

Video Output:

Number/type/connector Level (nominal)

Impedance

Sync:

Input/output type

Input level
Output level
Input Impedance
Output impedance
Propagation delay (max)
Rise/fall time (max)
Polarity

Bandwidth:

2 nS Positive or negative

3.0V to 5.0V p-p

TTL to 5.0V p-p

510 ohms

75 ohms

58 nS

>300kHz supporting up to 2048 x 1536

2 RGB + Sync/HD-15 male connector

Sync On Green, Composite Sync, Separate Sync (same as input)

@ 60Hz) QXGA

Max Cable Length: Approximately 50'

Power AC input: 115VAC, 50/60 Hz, 20 Watts

Mounting: Table top

Enclosure:

Type Metal

Dimensions / Weight 3.6" x 2.6" x 1" / 14 oz.

#### FSR Inc.

244 Bergen Boulevard, West Paterson, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207


Web: www.fsrinc.com · E-mail: sales@fsrinc.com

LIT 1124

### **ACCESSORIES:**

Each CDA-2 is supplied with a five foot (male-to-male) HD 15 monitor cable, and a UL and CSA approved power supply. To prevent the marring of furniture, rubber mounting feet are also provided.

# **TYPICAL OF CDA-2**



Specifications are subject to change without notice.

