# RQS-5C

## Color Quad Splitter with Alarm Interface



Our color quad splitter offers built-in motion detection and "On-Screen Display" (OSD) programming along with video compression and alarm inputs. It features freeze frame on all cameras, a camera sequencing option, and a security lock out button. A 117VAC/12V DC power supply is included.

## Specifications

| | |
|---|---|
| Camera Inputs | 4 inputs, 1.0 Vp.p Adjustable, 75 ohm terminated |
| Resolution | 1024 x 512 pixels |
| Alarm Input, Alarm Output, Recovery Input | 9 pin D-Sub type connector x 1 |
| Monitor Output | BNC X 1, composite video, 1.0 Vp-p, 75 ohms |
| VCR Output | BNC X 1, composite video, 1.0 Vp-p, 75 ohms |
| Viewing Options | Full Screen, Quadrant or Sequential |
| Digital Memory | 1024 x 512 pixels, Y=8 bit, C=8 bit |
| Display Rate | Real time refresh rate, 50/60 fields/second |
| Operation Humidity | 5% - 90% |
| Power Consumption | Max 11 watts |
| Power Supply | 12V DC adaptor included |
| Dimensions | 9.9"L x 13.5"W x 2.62"H |
| Weight | 4.9lbs |

**speco** technologies™

PROVIDEO™