

USER MANUAL

CSI/SPECO

INDEX

1.	INTRODUCTION	CTO
2.	FEATURES	3
3.	CONFIGURATION	4
4.	HOW TO INSTALL	5
5.	SPECIFICATIONS	6
6.	DIMENSIONS	7
7.	NOTICE	7


INTRODUCTION

The CVC-320WP waterproof CCTV camera is ideal for any outdoor application. This camera offers eight infrared LEDs which enable optimal viewing in a variety of lighting conditions.


FEATURE

- ◎ 1/3 ")NY Super-HAD CCD
- © 3.6mm fixed focus lens
- O Built-in electronic iris
- O Brass housing
- O Capable of underwater operation
- © 100% Naterproof (See specifications)

- 3 -



HOW TO INSTALL



Mount bracket with screws into wall or to other mounting surface



Attach the camera to the mounting bracket as shown left



Use the handle to adjust camera angle as shown left.

- 5 -

SPECIFICATIONS

MODEL NO. CVC-320WP

IMAGE SENSOR 1/3" SONY SUPER-HAD CCD SCANNING SYSTEM 525 LINE INTERLACE OUTPUT SIGNAL 1.0Vp-p/75ohm SYNC. NEGATIVE POLARITY

LIGHT SENSITIVITY 0.02 LUX

Zero lux when LEDs are active

RESOLUTION HORI: 420TV-LINE

LENS FIXED FOCUS LENS, f=3.6mm, F=2.0 STANDARD

AUTO-IRIS CONTROLLED BY

ELECTRONICS SYSTEM

SHUTTER SPEED 1/60-1/100,000

S/N RATIO 48dB OR MORE(AGC OFF)

GAMMA 0.45 AGC ON

IRIS

TEMP & HUMIDITY -10°C ~ °C °F · 20°F

BODY BRASS

CABLE LENGTH WITH 60FT CABLE

HOUSING COLOR BLACK

WEIGHT 210g (7.4 OZ) - WITHOUT CABLE

*Note: The cameras with LFDs operate in 0 lux when the LFDs are active.

THE RATED WATER DEPTH OF THE CAMERA FOR NORMAL OPERATION

APPROX. 20M (60FT.)

THE MAXIMUM OPERATING DEPTH

MAX. 30M (90FT)

THE CURRENT DRAIN FOR THE LFD ILLLIMINATION MAX. 100mA / 8 LFDs

AVERAGE 90mA / 8 LEDs

- 6 -

THE TOTAL CURRENT DRAIN FOR THE CAMERA INCLUDING LEDS

MAX. 200mA AT 12V DC AVERAGE 190mA AT 12V DC

THE MINIMUM AND MAXIMUM VOLTAGE FOR CAMERA


OPERATION

MIN 9V DC, MAX 16V DC

VARYING VOLTAGE TO THE LEDs AFFECTS THE LEVEL OF

ILLUMINATION

DIMENSIONS



NOTICE

ALWAYS USE DISCRETION WHEN INSTALLING MIDEO
AND/OR ALDIO SURMBILLANCE EQUIPMENT ESPECIALLY
WHEN THERE IS PERCEIVED PRIVACY, OR AN EXPECTATION
OF PRIVACY, INQUITE REGARDING FEDERAL, STATE AND/OR
LOCAL REGULATIONS APPLICABLE TO THE LAWFUL
INSTALLATION OF MIDEO AND/OR ALDIO RECORDING OR
SURVIBILLANCE EQUIPMENT. PARTY CONSENT MAY BE
REQUIRED.

- 7 -

CSI/SPECO

200 New Highway Amityville, NY 11701

Toll Free: 1-800-645-5516

In Metro NY: 631-957-8700

3B05035B Printed in Korea