Outdoor Motion Sensor Security Light Camera

Our CCD weatherproof outdoor camera is built into an outdoor light fixture and includes a built-in motion sensor for lighting control. It features low light sensitivity and high resolution. It has a wide angle lens with a built-in electronic shutter. A surface mount weatherproof electrical box further protects the unit. A mounting bracket, wiring harness and 12V DC power supply are included. This model is available with a white or bronze housing. Our outdoor motion sensor security light camera is available in both B/W and color.

Specifications

	B/W Version **CVC-340LC (Bronze Housing)** **CVC-340LC/W (White Housing)**	**Color Version** **CVC-640LC (Bronze Housing)** **CVC-640LC/W (White Housing)**
Image Device	1/3" B/W CCD image sensor	1/4" CCD image sensor
Resolution	420 lines	350 lines
Minimum Illumination	-02 lux	1.0 lux
Lens	3.6mm wide angle lens	3.6mm lens
Lens Option	2.5, 6, 8, 12mm	2.5, 6, 8, 12mm
Electronic Shutter	Auto 1/60 - 1/100,000 second	Auto 1/60 - 1/100,000 seconds
Motion Sensor	Controls lights	Controls lights
Mount	1/2" thread compatible with standard electrical boxes	1/2" thread compatible with standard electrical boxes
Bulbs	Light bulbs not included	Light bulbs not included
Operating Temperature	-14 degrees F to 122 degrees F	-14 degrees F to 122 degrees F
Output	Video BNC, power-DC jack	Video BNC, power-DC jack
Scanning Frequency	Horizontal 15.75 kHz vertical 60 Hz	horizontal 15.75 kHz vertical 60 Hz
Scanning System	EIA standard 525 line 60 fields	EIA standard 525 line 60 fields/second
Video Output Level	1.0 Vp-p 75 ohm	1.0 Vp-p 75 ohm
Video S/N Ratio	Greater than 46 dB	Greater than 46 dB
Power Consumption	100ma	100ma
Power Supply	Regulated 12V DC power supply included (UL and CSA listed)	regulated 12V DC power supply included (UL and CSA listed)
Overall Dimensions	7"L x 9.75"W x 8.5"H	7"L x 9.75"W x 8.5"H
Weight	12 1/2 lbs. (includes light housing)	12 1/2 lbs (includes light housing)

speco technologies™

PRO VIDEO™