
Specifications subject to change

CVC-95AM & CVC-695AM B/W or Color Angle Mount Camera



Our 1/3" B/W and Color CCD angle mount cameras are weather resistant and are encased in 18 gauge tamper-resistant stainless steel housings. The B/W version has a 0.02 lux low light sensitivity with 420 lines of resolution. The color version has a 1.0 lux low light sensitivity with 350 lines of resolution. They feature 3.6mm wide angle lenses that view at a downward angle of 38 degrees. They both have BNC video output. A tamperproof screw for vandal resistant mounting and 12V DC power supply are included. The color model is also offered in a version that has audio, which can be found under model number CVC-696AM/BK (with black case).

Specifications.

Resolution 420 lines Image Device

Electronic Shutter

Video S/N Ratio

Lens

Minimum Illumination Video Output Level

Output

Operating Temperature

Humidity

Power Consumption

Power Supply

Housing

Scanning Frequency

Dimensions

Weight

CVC-95CM

1/3" B/W CCD image sensor Auto 1/60 -1/100,000 second

3.6 mm wide angle lens,

Hor. 72°, Vert. 53°

0.02 lux

1.0 Vp.p, 75 ohm

Greater than 48 dB

Video - BNC, Power -DC jack, audio - RCA300mV@600 ohm

14° F to 122° F

Within 95% RH

150 mA

Regulated 12 V DC power supply included (UL and CSA listed)

18 gauge stainless steel

Horizontal 15.75 kHz vertical 60 Hz

2.5"L x 2.25"W x 2.75"H

6.8oz

CVC-695CM

350 lines

1/3" color CCD image sensor

Auto 1/60 -1/100,000 second

3.6 mm wide angle lens,

Hor. 72°, Vert. 53°

1.0 LUX

1.0 Vp.p, 75 ohm

Greater than 48 dB

Video - BNC, Power- DC jack,

audio - RCA 300mV@600 ohm

14° F to 122° F

Within 95% RH

210mA

Regulated 12 V DC power supply included (UL and CSA listed)

18 gauge stainless steel

Horizontal 15.75 kHz vertical 60 Hz

2.5"L x 2.25"W x 2.75"H

6.8oz



