

Multi-Application (MA) Series

5.25" or 6.5" 70/25V Commercial Speaker System



SP-6MA/T Shown

Speco Technologies' **Multi-Application (MA) Series** was designed with the focus of making the contractor's work as easy and time-efficient as possible.

Our all-in-one unit, pre-assembled with a back can and mounted transformer, features a quick flip 70 or 25 Volt selector switch and an easy select transformer wattage dial featuring the choice of 8 or 9 individual wattage tap settings covering your complete range of needs.

This fire-retardant, ABS unit also comes with insulated wires and has an attached metal safety loop and easy mount tabs for securing the unit.

The **MA Series** is the ideal all purpose, value sound solution covering a wide range of applications in commercial sound, and with a furnished 8 ohm tap selector, can be kept readily on hand to meet all your unexpected sound installation needs.

Specifications

	SP-5MA/T 5.25" 70/25V Commercial Speaker System	SP-6MA/T 6.5" 70/25V Commercial Speaker System
Woofer	5.25" Polypropylene with Rubber Surround	6.5" Polypropylene with Rubber Surround
Tweeter	1" Mylar Tweeter	1" Mylar Tweeter
Frequency	57Hz -20kHz	34Hz -20kHz
Power	30 Watt RMS/ 60 Watt Max	40 Watt RMS/ 80 Watt Max
Sensitivity	87 db 1w/1m	88 db 1w/1m
Impedance	8 ohms	8 ohms
Weight	4.5 lbs.	5.5 lbs
Transformer	70/25 Volt	70/25 Volt
Transformer Settings	30, 15, 7.5, 5, 2.5, 1, .50, .25, 8ohm	40, 30, 15, 7.5, 5, 2.5, 1, .50, .25, 8ohm
In-Ceiling Bracket Supports	BRC-6F	BRC-8F

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880